

HistoricBridges.org - National Bridge Inventory Data Sheet

2009 Inventory

The National Bridge Inventory contains data submitted by state transportation departments to the Federal Highway Administration in coded format.

Form Interface Design: www.historicbridges.org. Data Conversion Assistance By www.bridgehunter.com. None of the involved parties make any guarantee of accuracy.

Basic Information

Michigan [26]	Schoolcraft County [153]	Germfask [31940]	IN GERMFASK	46-14-49 = 46.246944	085-55-27 = - 85.924167
75200028000B010	Highway agency district: 1	Owner County Highway Agency [02]	Maintenance responsibility	County Highway Agency [02]	
Route 7558	TEN CURVES RD H44	Toll On free road [3]	Features intersected	MANISTIQUE RIVER	
Design - main 1	Concrete [1] Girder and floorbeam system [03]	Design - approach 0	Other [00]	Kilometerpoint 24.8 km = 15.4 mi	Year built 1928
				Year reconstructed N/A [0000]	Skew angle 20
				Structure Flared	Historical significance Bridge is on the NRHP. [1]
Total length 27.4 m = 89.9 ft	Length of maximum span 27.4 m = 89.9 ft	Deck width, out-to-out 7.7 m = 25.3 ft	Bridge roadway width, curb-to-curb 6.7 m = 22.0 ft		
Inventory Route, Total Horizontal Clearance 6.7 m = 22.0 ft	Curb or sidewalk width - left 0 m = 0.0 ft	Curb or sidewalk width - right 0 m = 0.0 ft			
Deck structure type	Concrete Cast-in-Place [1]				
Type of wearing surface	Bituminous [6]				
Deck protection					
Type of membrane/wearing surface					

Weight Limits

Bypass, detour length 2.6 km = 1.6 mi	Method to determine inventory rating	Load Factor(LF) [1]	Inventory rating 18.2 metric ton = 20.0 tons
	Method to determine operating rating	Load Factor(LF) [1]	Operating rating 32.7 metric ton = 36.0 tons
Bridge posting	Equal to or above legal loads [5]	Design Load	MS 18+Mod / HS 20+Mod [6]

Functional Details

Average Daily Traffic	673	Average daily truck traffi	0	%	Year	1999	Future average daily traffic	809	Year	2009
Road classification	Major Collector (Rural) [07]		Lanes on structure	2		Approach roadway width	9.1 m = 29.9 ft			
Type of service on bridge	Highway [1]		Direction of traffic	2 - way traffic [2]		Bridge median				
Parallel structure designation	No parallel structure exists. [N]									
Type of service under bridge	Waterway [5]		Lanes under structure	0		Navigation control				
Navigation vertical clearanc	0 = N/A		Navigation horizontal clearance	0 = N/A						
Minimum navigation vertical clearance, vertical lift bridge						Minimum vertical clearance over bridge roadway	99.99 m = 328.1 ft			
Minimum lateral underclearance reference feature	Feature not a highway or railroad [N]									
Minimum lateral underclearance on right	99.9 = Unlimited					Minimum lateral underclearance on left	0 = N/A			
Minimum Vertical Underclearance	0 = N/A		Minimum vertical underclearance reference feature	Feature not a highway or railroad [N]						
Appraisal ratings - underclearances	N/A [N]									

Repair and Replacement Plans

Type of work to be performed

Work done by

Bridge improvement cost

Roadway improvement cost

Length of structure improvement

Total project cost

Year of improvement cost estimate

Border bridge - state

Border bridge - percent responsibility of other state

Border bridge - structure number

Inspection and Sufficiency

Structure status	Open, no restriction [A]	Appraisal ratings - structural	Meets minimum tolerable limits to be left in place as is [4]
Condition ratings - superstructure	Poor [4]	Appraisal ratings - roadway alignment	Somewhat better than minimum adequacy to tolerate being left in place as is [5]
Condition ratings - substructure	Satisfactory [6]	Appraisal ratings - deck geometry	Meets minimum tolerable limits to be left in place as is [4]
Condition ratings - deck	Fair [5]		
Scour	Bridge foundations determined to be stable for the assessed or calculated scour condition. [8]		
Channel and channel protection	Bank protection is in need of minor repairs. River control devices and embankment protection have a little minor damage. Banks and/or channel have minor amounts of drift. [7]		
Appraisal ratings - water adequacy	Equal to present desirable criteria [8]	Status evaluation	Structurally deficient [1]
Pier or abutment protection		Sufficiency rating	33.4
Culverts	Not applicable. Used if structure is not a culvert. [N]		
Traffic safety features - railings	Inspected feature meets currently acceptable standards. [1]		
Traffic safety features - transitions	Inspected feature meets currently acceptable standards. [1]		
Traffic safety features - approach guardrail	Inspected feature meets currently acceptable standards. [1]		
Traffic safety features - approach guardrail ends	Inspected feature meets currently acceptable standards. [1]		
Inspection date	June 2008 [0608]	Designated inspection frequency	12 Months
Underwater inspection	Not needed [N]	Underwater inspection date	
Fracture critical inspection	Not needed [N]	Fracture critical inspection date	
Other special inspection	Not needed [N]	Other special inspection date	