

HistoricBridges.org - National Bridge Inventory Data Sheet

2012 Inventory

The National Bridge Inventory contains data submitted by state transportation departments to the Federal Highway Administration in coded format.

Form Interface Design: www.historicbridges.org. Data Conversion Assistance By www.bridgehunter.com. None of the involved parties make any guarantee of accuracy.

Basic Information

California [06]	Sonoma County [097]	Unknown [00000]	0.4 MI W OF DRY CREEK RD	38-39-14 = 38.653889	122-55-40 = - 122.927778
20C0248	Highway agency district 4	Owner County Highway Agency [02]	Maintenance responsibility	County Highway Agency [02]	
Route 0		LAMBERT BRIDGE RD	Toll On free road [3]	Features intersected DRY CREEK	
Design - main	Steel [3]	Design - approach		Kilometerpoint	0 km = 0.0 mi
1	Truss - Thru [10]	0	Other [00]	Year built	1915
				Year reconstructed	N/A [0000]
				Skew angle	0
				Structure Flared	
				Historical significance	Bridge is eligible for the NRHP. [2]
Total length	57.9 m = 190.0 ft	Length of maximum span	56.4 m = 185.0 ft	Deck width, out-to-out	5.2 m = 17.1 ft
Inventory Route, Total Horizontal Clearance	5 m = 16.4 ft	Curb or sidewalk width - left	0 m = 0.0 ft	Curb or sidewalk width - right	0 m = 0.0 ft
Deck structure type	Concrete Cast-in-Place [1]				
Type of wearing surface					
Deck protection					
Type of membrane/wearing surface					

Weight Limits

Bypass, detour length	Method to determine inventory rating	Allowable Stress(AS) [2]	Inventory rating	0 metric ton = 0.0 tons
1.8 km = 1.1 mi	Method to determine operating rating	Allowable Stress(AS) [2]	Operating rating	14.3 metric ton = 15.7 tons
	Bridge posting		Design Load	

Functional Details

Average Daily Traffic	1200	Average daily truck traffi	1	%	Year	2008	Future average daily traffic	838	Year	2029
Road classification	Local (Rural) [09]		Lanes on structure	1		Approach roadway width	5.8 m = 19.0 ft			
Type of service on bridge	Highway [1]		Direction of traffic	One lane bridge for 2 - way traffic [3]		Bridge median				
Parallel structure designation	No parallel structure exists. [N]									
Type of service under bridge	Waterway [5]		Lanes under structure	0		Navigation control				
Navigation vertical clearanc	0 = N/A		Navigation horizontal clearance	0 = N/A						
Minimum navigation vertical clearance, vertical lift bridge			Minimum vertical clearance over bridge roadway	3.98 m = 13.1 ft						
Minimum lateral underclearance reference feature	Feature not a highway or railroad [N]									
Minimum lateral underclearance on right	0 = N/A					Minimum lateral underclearance on left	0 = N/A			
Minimum Vertical Underclearance	0 = N/A		Minimum vertical underclearance reference feature	Feature not a highway or railroad [N]						
Appraisal ratings - underclearances	N/A [N]									

Repair and Replacement Plans

Type of work to be performed	Work done by	Work to be done by contract [1]		
Replacement of bridge or other structure because of substandard load carrying capacity or substantial bridge roadway geometry. [31]	Bridge improvement cost	690000	Roadway improvement cost	138000
	Length of structure improvement	57.9 m = 190.0 ft	Total project cost	1159000
	Year of improvement cost estimate	2010		
	Border bridge - state		Border bridge - percent responsibility of other state	
	Border bridge - structure number			

Inspection and Sufficiency

Structure status

Posted for load [P]

Appraisal ratings -
structural

Basically intolerable requiring high priority of replacement [2]

Condition ratings - superstructure

Serious [3]

Appraisal ratings -
roadway alignment

Basically intolerable requiring high priority of corrective action [3]

Condition ratings - substructure

Fair [5]

Appraisal ratings -
deck geometry

Basically intolerable requiring high priority of replacement [2]

Condition ratings - deck

Satisfactory [6]

Scour

Bridge foundations determined to be stable for the assessed or calculated scour condition. [8]

Channel and channel protection

Bank protection is in need of minor repairs. River control devices and embankment protection have a little minor damage. Banks and/or channel have minor amounts of drift. [7]

Appraisal ratings - water adequacy

Better than present minimum criteria [7]

Status evaluation

Structurally deficient [1]

Pier or abutment protection

Sufficiency rating

4.8

Culverts

Not applicable. Used if structure is not a culvert. [N]

Traffic safety features - railings

Traffic safety features - transitions

Traffic safety features - approach guardrail

Traffic safety features - approach guardrail ends

Inspection date

July 2011 [0711]

Designated inspection frequency

12

Months

Underwater inspection

Not needed [N]

Underwater inspection date

Fracture critical inspection

Every two years [Y24]

Fracture critical inspection date

December 2011 [1211]

Other special inspection

Not needed [N]

Other special inspection date