The National Bridge Inventory contains data submitted by state transportion departments to the Federal Highway Administration in coded format.

Form Interface Design: www.historicbridges.org. Data Conversion Assistance By www.bridgehunter.com. None of the involved parties make any guarantee of accuracy.

Basic Information						
Illinois [17] DuPage County [043]		Hinsdale [35307]	300 FT N CHICAGO AVE		41-48-17 = 41.8 087-55-12 = -87.9	
000022655029041 Highway agency district 1		Owner Railroad [27]	ner Railroad [27] Maintenance responsibility		Railroad [27]	
Route 1150	OAK S	Т	Toll On fre	e road [3] Feat	ures intersected BN RR	
Design - Steel [3] main Girder and floor	orbeam system [03]	approach	or timber [7] er/Multi-beam or girder [02]	Kilometerpoint 33.8 km Year built 1910 Skew angle 14 Historical significance	m = 21.0 mi Year reconstructed Structure Flared Bridge is eligible for	
Total length 33.5 m = 1 Inventory Route, Total H		yth of maximum spa 4.5 m = 14.8 ft	n 14 m = 45.9 ft Curb or sidewalk wi	Deck width, out-to-out	7 m = 23.0 ft Bridge	e roadway width, curb-to-curb $\begin{bmatrix} 4.6 \text{ m} = 15.1 \text{ ft} \end{bmatrix}$ r sidewalk width - right $\begin{bmatrix} 1.5 \text{ m} = 4.9 \text{ ft} \end{bmatrix}$
Deck structure type Type of wearing surface Deck protection		ood or Timber [8] uminous [6]				
Type of membrane/wear	ing surface					
Weight Limits						
Bypass, detour length 0.3 km = 0.2 mi	i viction to determine inventory rating		Allowable Stress(AS) Allowable Stress(AS)		, ,	ton = 15.8 tons ton = 21.8 tons
Bridge posting				Design	n Load	

Functional Details							
Average Daily Traffic 309 Average daily tru	uck traffi 0 % Year 1998 Future average daily traffic 1000 Year 2020						
Road classification Local (Urban) [19]	Lanes on structure 1 Approach roadway width 8.5 m = 27.9 ft						
Type of service on bridge Highway [1]	Direction of traffic One lane bridge for 2 - way traffic [3] Bridge median						
Parallel structure designation No parallel structure	e exists. [N]						
Type of service under bridge Railroad [2]	Lanes under structure 0 Navigation control Not applicable, no waterway. [N]						
Navigation vertical clearance 0 = N/A Navigation horizontal clearance 0 = N/A							
Minimum navigation vertical clearance, vertical lift bridge Minimum vertical clearance over bridge roadway 99.99 m = 328.1 ft							
Minimum lateral underclearance reference feature Railroad beneath structure [R]							
Minimum lateral underclearance on right 2.4 m = 7.9 ft Minimum lateral underclearance on left 0 = N/A							
Minimum Vertical Underclearance 6.1 m = 20.0 ft Minimum vertical underclearance reference feature Railroad beneath structure [R]							
Appraisal ratings - underclearances Meets minimum tolerable limits to be left in place as is [4]							
Repair and Replacement Plans							
Type of work to be performed	Work done by Work to be done by contract [1]						
Replacement of bridge or other structure because of substandard load carrying capacity or substantial	Bridge improvement cost 223000 Roadway improvement cost 22000						
bridge roadway geometry. [31]	Length of structure improvement 43.6 m = 143.1 ft Total project cost 335000						
	Year of improvement cost estimate						
	Border bridge - state Border bridge - percent responsibility of other state						
	Border bridge - structure number						

Inspection and Sufficiency								
Structure status Posted for lo	ad [P]	Appraisal ratings - structural	Meets minimum tolerable limits to be left in place as is [4]					
Condition ratings - superstructur	ondition ratings - superstructur Poor [4]		Basically intolerable requiring	high priority of replacement [2]				
Condition ratings - substructure Fair [5]		Appraisal ratings -	Basically intolerable requiring	high priority of replacement [2]				
Condition ratings - deck	Satisfactory [6]	deck geometry						
Scour	Bridge not over v	er waterway. [N]						
Channel and channel protection	Not applicable. [I	N]						
Appraisal ratings - water adequace	N/A [N]		Status evaluation	Structurally deficient [1]				
Pier or abutment protection			Sufficiency rating	22.7				
Culverts Not applicable. Used	if structure is not a culve	rt. [N]						
Traffic safety features - railings								
Traffic safety features - transition	IS	Inpected feature meets currently acceptable standards. [1]						
Traffic safety features - approach	n guardrail	Inpected feature meets currently acceptable standards. [1]						
Traffic safety features - approach								
Inspection date August 2008	[0808] Desi	gnated inspection frequency 24	nspection frequency 24 Months					
Underwater inspection	Not needed [N]	Underwater inspe	Underwater inspection date					
Fracture critical inspection	Not needed [N]	Fracture critical in	Fracture critical inspection date					
Other special inspection	Not needed [N]	Other special insp	pection date					