

HistoricBridges.org - National Bridge Inventory Data Sheet

2012 Inventory

The National Bridge Inventory contains data submitted by state transportation departments to the Federal Highway Administration in coded format.

Form Interface Design: www.historicbridges.org. Data Conversion Assistance By www.bridgehunter.com. None of the involved parties make any guarantee of accuracy.

Basic Information

Indiana [18]	Ripley County [137]	Unknown [00000]	00.24 E of CR 1000W	39-11-24 = 39.190000	085-26-07 = - 85.435278
6900109	Highway agency district 5	Owner County Highway Agency [02]	Maintenance responsibility	County Highway Agency [02]	
Route 56		BROWNSTOWN ROAD	Toll On free road [3]	Features intersected VERNON FK MUSCATATUCK R.	
Design - main	Concrete [1]	Design - approach		Kilometerpoint 0 km = 0.0 mi	
3	Stringer/Multi-beam or girder [02]	0	Other [00]	Year built 1926	Year reconstructed #Num!
				Skew angle 0	Structure Flared
				Historical significance Bridge is eligible for the NRHP. [2]	
Total length 30.2 m = 99.1 ft	Length of maximum span 9.8 m = 32.2 ft	Deck width, out-to-out 5.8 m = 19.0 ft	Bridge roadway width, curb-to-curb 4.9 m = 16.1 ft		
Inventory Route, Total Horizontal Clearance 4.9 m = 16.1 ft	Curb or sidewalk width - left 0 m = 0.0 ft	Curb or sidewalk width - right 0 m = 0.0 ft			
Deck structure type	Concrete Cast-in-Place [1]				
Type of wearing surface	Bituminous [6]				
Deck protection					
Type of membrane/wearing surface					

Weight Limits

Bypass, detour length 0.3 km = 0.2 mi	Method to determine inventory rating	No rating analysis performed [5]	Inventory rating	0 metric ton = 0.0 tons
	Method to determine operating rating	No rating analysis performed [5]	Operating rating	0 metric ton = 0.0 tons
	Bridge posting		Design Load	

Functional Details

Average Daily Traffic	0	Average daily truck traffi	0	%	Year	2010	Future average daily traffic	100	Year	2030
Road classification	Local (Rural) [09]			Lanes on structure	1		Approach roadway width	4.9 m = 16.1 ft		
Type of service on bridge	Highway [1]			Direction of traffic	One lane bridge for 2 - way traffic [3]		Bridge median			
Parallel structure designation	No parallel structure exists. [N]									
Type of service under bridge	Waterway [5]		Lanes under structure	0		Navigation control				
Navigation vertical clearanc	0 = N/A			Navigation horizontal clearance	0 = N/A					
Minimum navigation vertical clearance, vertical lift bridge				Minimum vertical clearance over bridge roadway	99.99 m = 328.1 ft					
Minimum lateral underclearance reference feature	Feature not a highway or railroad [N]									
Minimum lateral underclearance on right	0 = N/A					Minimum lateral underclearance on left	0 = N/A			
Minimum Vertical Underclearance	0 = N/A			Minimum vertical underclearance reference feature	Feature not a highway or railroad [N]					
Appraisal ratings - underclearances	N/A [N]									

Repair and Replacement Plans

Type of work to be performed	Work done by	Work to be done by contract [1]		
Replacement of bridge or other structure because of substandard load carrying capacity or substantial bridge roadway geometry. [31]	Bridge improvement cost	550000	Roadway improvement cost	350000
	Length of structure improvement	38.1 m = 125.0 ft	Total project cost	900000
	Year of improvement cost estimate	2010		
	Border bridge - state		Border bridge - percent responsibility of other state	
	Border bridge - structure number			

Inspection and Sufficiency

Structure status

Bridge closed to all traffic [K]

Appraisal ratings -
structural

Condition ratings - superstructure

Appraisal ratings -
roadway alignment

Meets minimum tolerable limits to be left in place as is [4]

Condition ratings - substructure

Appraisal ratings -
deck geometry

Basically intolerable requiring high priority of corrective action [3]

Condition ratings - deck

Imminent Failure [1]

Scour

Bridge is scour critical; bridge foundations determined to be unstable. [3]

Channel and channel protection

Bank and embankment protection is severely undermined. River control devices have severe damage. Large deposits of debris are in the channel. [4]

Appraisal ratings - water adequacy

Equal to present minimum criteria [6]

Status evaluation

Structurally deficient [1]

Pier or abutment protection

Sufficiency rating

24.5

Culverts

Not applicable. Used if structure is not a culvert. [N]

Traffic safety features - railings

Traffic safety features - transitions

Traffic safety features - approach guardrail

Traffic safety features - approach guardrail ends

Inspection date

November 2010 [1110]

Designated inspection frequency

24

Months

Underwater inspection

Not needed [N]

Underwater inspection date

Fracture critical inspection

Not needed [N]

Fracture critical inspection date

Other special inspection

Not needed [N]

Other special inspection date