HistoricBridges.org - National Bridge Inventory Data Sheet

2015 Inventory

The National Bridge Inventory contains data submitted by state transportion departments to the Federal Highway Administration in coded format.
Form Interface Design: www.historicbridges.org. Data Conversion Assistance By www.bridgehunter.com. None of the involved parties make any guarantee of accuracy.

Basic Information

Iowa [19]	Buchanan County [019]	Unknown [00000]	87101303	42-21-02.71 = 42.350753	091-57-59.45 = -91.966514

000000000081560 | Highway agency district: 0 | Owner: County Highway Agency [02] | Maintenance responsibility: County Highway Agency [02]

Route: 0 | LOCAL 305TH ST. | Toll: On free road [3] | Features intersected: LIME CR

Design - main	Steel [3]	Design - approach		Kilometerpoint	0 km = 0.0 mi
1	Truss - Thru [10]	0	Other [00]	Year built: 1910	Year reconstructed: N/A [0000]
				Skew angle: 0	Structure Flared:
				Historical significance	Bridge is possibly eligible for the NRHP. [3]

Total length	24.7 m = 81.0 ft	Length of maximum span	24.4 m = 80.1 ft	Deck width, out-to-out	4.8 m = 15.7 ft	Bridge roadway width, curb-to-curb	4.7 m = 15.4 ft
Inventory Route, Total Horizontal Clearance	4.6 m = 15.1 ft	Curb or sidewalk width - left	0 m = 0.0 ft	Curb or sidewalk width - right	0 m = 0.0 ft		

Deck structure type	Wood or Timber [8]
Type of wearing surface	Wood or Timber [7]
Deck protection	
Type of membrane/wearing surface	

Weight Limits

Bypass, detour length	Method to determine inventory rating	Allowable Stress(AS) [2]	Inventory rating	6.3 metric ton = 6.9 tons	
0.6 km = 0.4 mi	Method to determine operating rating	Allowable Stress(AS) [2]	Operating rating	10.8 metric ton = 11.9 tons	
	Bridge posting		Design Load		

Functional Details

Average Daily Traffic	15	Average daily truck traffi	0 %	Year	2013	Future average daily traffic	15
Year	2033						
Road classification	Local (Rural) [09]	Lanes on structure	1	Approach roadway width	7.3 m = 24.0 ft		
Type of service on bridge	Highway [1]	Direction of traffic	One lane bridge for 2 - way traffic [3]	Bridge median			
Parallel structure designation	No parallel structure exists. [N]						
Type of service under bridge	Waterway [5]	Lanes under structure	0	Navigation control			
Navigation vertical clearanc	0 = N/A	Navigation horizontal clearance	0 = N/A				
Minimum navigation vertical clearance, vertical lift bridge	0 m = 0.0 ft	Minimum vertical clearance over bridge roadway	2.74 m = 9.0 ft				
Minimum lateral underclearance reference feature	Feature not a highway or railroad [N]						
Minimum lateral underclearance on right	0 = N/A	Minimum lateral underclearance on left	0 = N/A				
Minimum Vertical Underclearance	0 = N/A	Minimum vertical underclearance reference feature	Feature not a highway or railroad [N]				
Appraisal ratings - underclearances	N/A [N]						

Repair and Replacement Plans

Type of work to be performed

Replacement of bridge or other structure because of substandard load carrying capacity or substantial bridge roadway geometry. [31]

Work done by	Work to be done by contract [1]		
Bridge improvement cost	179000	Roadway improvement cost	30000
Length of structure improvement	105 m = 344.5 ft	Total project cost	
Year of improvement cost estimate			
Border bridge - state		Border bridge - percent responsibility of other state	
Border bridge - structure number			

Inspection and Sufficiency

Structure status	Posted for load [P]	Appraisal ratings - structural	Basically intolerable requiring high priority of replacement [2]
Condition ratings - superstructure	Serious [3]	Appraisal ratings - roadway alignment	Meets minimum tolerable limits to be left in place as is [4]
Condition ratings - substructure	Poor [4]	Appraisal ratings - deck geometry	Basically intolerable requiring high priority of replacement [2]
Condition ratings - deck	Serious [3]		
Scour	Bridge foundations determined to be stable for assessed or calculated scour condition. [5]		
Channel and channel protection	Bank is beginning to slump. River control devices and embankment protection have widespread minor damage. There is minor stream bed movement evident. Debris is restricting the channel slightly. [6]		
Appraisal ratings - water adequacy	Meets minimum tolerable limits to be left in place as is [4]	Status evaluation	Structurally deficient [1]
Pier or abutment protection		Sufficiency rating	0
Culverts	Not applicable. Used if structure is not a culvert. [N]		
Traffic safety features - railings			
Traffic safety features - transitions			
Traffic safety features - approach guardrail			
Traffic safety features - approach guardrail ends			
Inspection date	December 2013 [1213]	Designated inspection frequency	12 Months
Underwater inspection	Not needed [N]	Underwater inspection date	
Fracture critical inspection	Every year [Y12]	Fracture critical inspection date	December 2013 [1213]
Other special inspection	Not needed [N]	Other special inspection date	