

# HistoricBridges.org - National Bridge Inventory Data Sheet

2019 Inventory

The National Bridge Inventory contains data submitted by state transportation departments to the Federal Highway Administration in coded format.

Form Interface Design: www.historicbridges.org. Data Conversion Assistance By www.bridgehunter.com. None of the involved parties make any guarantee of accuracy.

## Basic Information

Louisiana [22]	Vermilion Parish [113]	Abbeville [00100]	0.13 MI W OF US 167	29-58-30.83 = 29.975231	092-08-22.42 = -92.139561
35700550600131	Highway agency district: 3	Owner State Highway Agency [01]	Maintenance responsibility	State Highway Agency [01]	
Route 14	LA0014B	Toll On free road [3]	Features intersected VERMILION R/ABBEVILLE		
Design - main 1	Steel [3] Movable - Lift [15]	Design - approach 4	Concrete [1] Tee beam [04]	Kilometerpoint 20.4 km = 12.6 mi	Year built 1938 Year reconstructed N/A [0000]
			Skew angle 0	Structure Flared	
			Historical significance Bridge is eligible for the NRHP. [2]		
Total length	73.5 m = 241.2 ft	Length of maximum span	22.9 m = 75.1 ft	Deck width, out-to-out	10.9 m = 35.8 ft
Inventory Route, Total Horizontal Clearance	9.1 m = 29.9 ft	Curb or sidewalk width - left	1.5 m = 4.9 ft	Curb or sidewalk width - right	1.5 m = 4.9 ft
Deck structure type	Open Grating [3]				
Type of wearing surface					
Deck protection					
Type of membrane/wearing surface					

## Weight Limits

Bypass, detour length 0.3 km = 0.2 mi	Method to determine inventory rating	Load Factor(LF) [1]	Inventory rating	13.6 metric ton = 15.0 tons
	Method to determine operating rating	Load Factor(LF) [1]	Operating rating	28.1 metric ton = 30.9 tons
Bridge posting	20.0 - 29.9 % below [2]		Design Load	M 13.5 / H 15 [2]

## Functional Details

Average Daily Traffic	8700	Average daily truck traffi	10	%	Year	2016	Future average daily traffic	10962	Year	2036
Road classification	Other Principal Arterial (Urban) [14]		Lanes on structure	2		Approach roadway width	10.4 m = 34.1 ft			
Type of service on bridge	Highway [1]		Direction of traffic	2 - way traffic [2]		Bridge median				
Parallel structure designation	No parallel structure exists. [N]									
Type of service under bridge	Waterway [5]		Lanes under structure	0		Navigation control	Navigation control on waterway (bridge permit required). [1]			
Navigation vertical clearanc	17.1 m = 56.1 ft			Navigation horizontal clearance	13.4 m = 44.0 ft					
Minimum navigation vertical clearance, vertical lift bridge	7 m = 23.0 ft				Minimum vertical clearance over bridge roadway	4.55 m = 14.9 ft				
Minimum lateral underclearance reference feature	Feature not a highway or railroad [N]									
Minimum lateral underclearance on right	0 = N/A					Minimum lateral underclearance on left	0 = N/A			
Minimum Vertical Underclearance	0 = N/A			Minimum vertical underclearance reference feature	Feature not a highway or railroad [N]					
Appraisal ratings - underclearances	N/A [N]									

## Repair and Replacement Plans

Type of work to be performed	Work done by	Work to be done by contract [1]		
Replacement of bridge or other structure because of substandard load carrying capacity or substantial bridge roadway geometry. [31]	Bridge improvement cost	704000	Roadway improvement cost	
	Length of structure improvement	82.6 m = 271.0 ft	Total project cost	1056000
	Year of improvement cost estimate	2016		
	Border bridge - state		Border bridge - percent responsibility of other state	
	Border bridge - structure number			

## Inspection and Sufficiency

Structure status	Posted for load [P]	Appraisal ratings - structural	Basically intolerable requiring high priority of replacement [2]
Condition ratings - superstructure	Satisfactory [6]	Appraisal ratings - roadway alignment	Equal to present minimum criteria [6]
Condition ratings - substructure	Satisfactory [6]	Appraisal ratings - deck geometry	Basically intolerable requiring high priority of replacement [2]
Condition ratings - deck	Satisfactory [6]		
Scour	Bridge foundations determined to be stable for assessed or calculated scour condition. [5]		
Channel and channel protection	Banks are protected or well vegetated. River control devices such as spur dikes and embankment protection are not required or are in a stable condition. [8]		
Appraisal ratings - water adequacy	Equal to present desirable criteria [8]	Status evaluation	Structurally deficient [1]
Pier or abutment protection	In place but in a deteriorated condition [3]	Sufficiency rating	47.6
Culverts	Not applicable. Used if structure is not a culvert. [N]		
Traffic safety features - railings			
Traffic safety features - transitions			
Traffic safety features - approach guardrail			
Traffic safety features - approach guardrail ends			
Inspection date	May 2017 [0517]	Designated inspection frequency	24 Months
Underwater inspection	Unknown [Y60]	Underwater inspection date	August 2018 [0818]
Fracture critical inspection	Not needed [N]	Fracture critical inspection date	
Other special inspection	Every year [Y12]	Other special inspection date	May 2018 [0518]