Massachusetts Cultural Resource Information System

Scanned Record Cover Page

Inventory No: LAW.902

Historic Name: Duck Bridge - Union Street Bridge

Common Name:

Address:

City/Town: Lawrence

Village/Neighborhood: Lawrence

Local No: 991

Year Constructed:

Architect(s): Boston Bridge Works

Architectural Style(s):

Use(s): Other Engineering; Other Transportation

Significance: Engineering; Transportation


LAW.A: North Canal Historic District

Area(s): LAW.W: North Canal Historic District (Boundary

Increase)

Designation(s): Nat'l Register District (11/13/1984); Nat'l Register District

(5/8/2009)



The Massachusetts Historical Commission (MHC) has converted this paper record to digital format as part of ongoing projects to scan records of the Inventory of Historic Assets of the Commonwealth and National Register of Historic Places nominations for Massachusetts. Efforts are ongoing and not all inventory or National Register records related to this resource may be available in digital format at this time.

The MACRIS database and scanned files are highly dynamic; new information is added daily and both database records and related scanned files may be updated as new information is incorporated into MHC files. Users should note that there may be a considerable lag time between the receipt of new or updated records by MHC and the appearance of related information in MACRIS. Users should also note that not all source materials for the MACRIS database are made available as scanned images. Users may consult the records, files and maps available in MHC's public research area at its offices at the State Archives Building, 220 Morrissey Boulevard, Boston, open M-F, 9-5.

Users of this digital material acknowledge that they have read and understood the MACRIS Information and Disclaimer (http://mhc-macris.net/macrisdisclaimer.htm)

Data available via the MACRIS web interface, and associated scanned files are for information purposes only. THE ACT OF CHECKING THIS DATABASE AND ASSOCIATED SCANNED FILES DOES NOT SUBSTITUTE FOR COMPLIANCE WITH APPLICABLE LOCAL, STATE OR FEDERAL LAWS AND REGULATIONS. IF YOU ARE REPRESENTING A DEVELOPER AND/OR A PROPOSED PROJECT THAT WILL REQUIRE A PERMIT, LICENSE OR FUNDING FROM ANY STATE OR FEDERAL AGENCY YOU MUST SUBMIT A PROJECT NOTIFICATION FORM TO MHC FOR MHC'S REVIEW AND COMMENT. You can obtain a copy of a PNF through the MHC web site (www.sec.state.ma.us/mhc) under the subject heading "MHC Forms."

Commonwealth of Massachusetts
Massachusetts Historical Commission
220 Morrissey Boulevard, Boston, Massachusetts 02125
www.sec.state.ma.us/mhc

This file was accessed on:

Friday, March 07, 2014 at 3:29: AM

HISTORIC BRIDGE INVENTORY & EVALUATION

LAW 902

DUCK BRIDGE

	·		. Das	te:5/	/19/80	
Mun	icipality	LAWRENCE				·X
Str	eet Name	& Route #	UNION ST.			
	Over	MERRIMACK RIV	TER		. •	
		& Route #		431		
Bri	dge No.	L-4-3	Bridge K	ey # 255-514	-002 100	Dist. 5
		CRITERIA FOR	DETERMINATION	OF HISTORIC	SIGNIFICANCE	
· 1.	Builders	Contribution	•	for OTHCAA	ing: 140 (1-10:8	6)
	Quantity			•		
	Unknown		Severa	1(1-10)	ManyX	or moral
	Name of	Builder:	BOSTON BRIDGE WORKS	(plate)	•.	o or more,
			George L V	-	engineer (plate)	
II.	•		X No1850-1900 1		1 0 3 n	
III.	Bridge ty Bridge Warden Lea Total Lea Number of Patented Load Carr Configura	Double hold pe Steel trustidth 49.0 mgth of Bridge f Spans: 5	s — Waru the Span No Y: Adequate	Lengths 1 Unknown	es riveted no	114.0,114.0,126
	List Spec	cial Features	and Modification	: ons:	•	
	original	y had timber office	igers and deck, steel	grid deck put	in 1939.	

BRIDGES PREVIOUSLY REVIEWED BY M.H.C. -- CONCURRENCE REAFFIRMED

	Municipality	On/Over	Br. Dept. No.
Bridge:	Lawrence	Union St./Merrimack R.	L-4-3
was dete		Potentially eligible	Historical Commission and
After a	review of all kno	own bridges of comparable :	structural type identified
in the M	.D.P.W. statewide	computerized database; 4	ne M.D.P.W. now reaffirms
its conc	urrence with that	initial determination.	
Summary The one of only more open Dridge Warnell city	olded of 21 War y 8 (out of 194) ino; built by orko); and an in of Lawrence. Or	ifficance: Then through thus bridges in the metal truss bridges in the an important Massachusetto tegral part, both visually arms of the earliest riveted trusted the	identified in the MDPW database MDPW database to include 5 o bridge-building firm (Booton and historically, of the historic so bridges in the database
Statemen Date: _8	t prepared by:	5. J. Roper, MDPW History	

HISTORIC BRIDGE INVENTORY & EVALUATION

LAW. 902

DUCK BRIDGE

			Date	5/1	.9/80	
Mun	icinality	TAWRENCE				н. х
			UNION ST.			
	Over	MERRIMACK RIVE	R			
Str	eet Name &	Route #			***************************************	
Bri	dge No.	I-4-3	Bridge Key	# 895-514-0	002 100	Dist. 5
			DETERMINATION OF			3
ı.	Builders	Contribution				
	Quantity				*	
	Unknown _	•	Several		Many	
	Name of B		STON BRIDGE WORKS		()	lo or more)
		esigner:		*,.		
	P	laque: Yes	X No.			
II.		-	1850-1900 1887			1.66
III.	TECHNICAL Bridge type Bridge Wie	e Steel truss dth 49.0	Warren throw	igh true		
	Total Len	ath of Bridge	C7 0 7 .			114.0.114.0.126
*	Patented:	Yes	Span Le	known	X 114.0,	
	Configura	ying Capacity: tion: Unique_ Materials:	Adequate Unusual	X Co	adequate	

List Special Features and Modifications:

IV.	ENVIRONMENTAL
	Aesthetics: Unusual Good Common Violated Wiolated History of Bridge and Area:
	See Attached sheets
v.	ECONOMICS
	Owner: Municipal County State Federal R.R.
	What is your recommendation? Maintenance Replacement Rehabilitation Are materials available for Rehabilitation: Yes No Is structure scheduled for replacement? Yes No
VI.	PHOTOS - INDICATE SHOTS TAKEN
II.	1. Setting 2. Builders Plaque 3. 3/4 View 4. Thru View 5. Under View 6. Elevation 7. Joint & Connections 8. Machinery 9. Decorative Features 6. Elevation 7. Joint & Connections 8. Machinery 9. Decorative Features
· .	 In your judgement, does this bridge have historic value? YesNo. Please explain your answer to #1
	3. Additional Comments required on back of page.
Prepa Title	

DUCK BRIDGE AND APPROACHES R.R.E. 1942

By Chapter 265 of the Acts of 1854 George L. Davis and other were incorporated as the proprietors of Lawrence Bridge and authorized to erect a bridge at Union Street which either the County Commissioners or the City of Lawrence might purchase after five year provided they purchased or offered to purchase Andover Bridge. In 1854 also the County Commissioners laid out Union Street "to the southerly end of said bridge" four rods wide, the center line coinciding with the center line of the bridge then being erected.

In 1856 it appeared that the city of Lawrence in building the road had neglected filling a portion of said road "near the new bridge", and the county did the work and ordered the city to reimburse it in the sum of \$899.80.

By authority of Chapter 309 of the Acts of 1868 the County Commissioners laid out the Lawrence Bridge as a public highway, ordered damages paid and ordered the city to maintain the bridge.

Chapter 299 of the Acts of 1887 authorized the city of Lawrence to borrow a sum of money not exceeding \$75,000 to reconstruct the Union Street Bridge. It is not known what records there may be in the city of Lawrence relating to the rebuilding of the bridge at this time. There are no records in the county files, but in 1886 the County Commissioners under authority of Chapter 106 of the Acts of 1888 reimbursed the city of Lawrence a part of the cost of the bridge. It was thereafter maintained by the city until 1910 when full control was placed in the County Commissioners by authority of Chapter 434 of the Acts of that year (which related to both Duck Bridge and Falls Bridge) and

shall have full control of both bridges and shall" etc. The abutment wall on the south side now forms a part of a continuous wall on which the buildings both up and down stream are supported, whether there are, or ever were, wing walls extending back inland is not apparent, and we have no records to show it. On the north side the building east of the bridge extends considerably further out into the stream, but here also there is nothing to indicate whether there are, or ever were, other wing walls.

By Chapter 314 of the Acts of 1939 the County Commissioners, were authorized to rebuild the roadway floor to consist of an open steel grid or mesh floor, and this was done.

See also Highway Index for action by the County Commissioners previous to 1910, and Bridge Schedule for record of contracts, agreements, etc. since that date.

DUCK BRIDGE

Load capacity and posting

There is no information in the county files as to the load capacity for which the bridge was originally designed. The trusses and floor beams, except for repairs, are as originally built, but the original wooden stringers have been replaced by steel stringers and the roadway deck is now of the steel grid type.

Reports of George F. Swain, LL D., are on file in 067C in 1920 when the original wooden stringers were still there and in 1928 when it was proposed to replace a part of them by steel stringers, and there is a report relating to the sidewalks by J. R. Worcester in 1933 in 067C. It is believed that the roadway is good for the fourteen ton load allowed by law, and the bridge is not posted. (See vote of County Commissioners March 2, 1934).











NO DATE, CA. 1980








NU DATE, CA. 1980

1. NAME OF STRUCTURE Union Street Bridge (Duck Bridge) 5. LOCATION: STREET & NUMBER between Union & South Union Streets CITY OR TOWN COUNTY Lawrence Essex ADDRESS	RE 4. INDUSTRIAL CLASSIFICATION 602
between Union & South Union Streets Lawrence Essex	CTATE
7. UWNER OF PROPERTY ADDRESS	MA 6. USGS QUAD MAP & UTM GRID REF. Lawrence
	19.323060. 473000
8. CONDITION: XEXCELLENT GOOD FAIR DETERIORATED RUINS	UNEXPOSED ALTERED ACCESSIBLE TO PUBLIC
9. DESCRIPTION & BACKGROUND HISTORY: NUMBER OF STRUCTURES; DIMENSIONS; FABRIC; STRUCTURE & FORM; SURV	•
EQUIPMENT; APPROX. AREA OF SITE; ALTERATIONS; PRESENT USE; ENGINEER/ ARCHITECT/DESIGNER; IMPORTANT EVE	
The Union Street bridge was built in 1888 by the Boston Bridge Works. The Union Street bridge was built in 1888 by the Boston Bridge Works.	
intended for foot and wheeled traffic between north and south Lawrence, ac Parallel chord, riveted, double intersection Warren truss bridge, with 5 s	
block, cutwater style piers, and two granite block pier abutments. The pi	
earlier bridge during the 1850s. The bridge is of lattice and plate girder	
The floor was probably originally of wood, but is now a steel lattice deck.	The upper lateral system is a double
intersection Warren truss. The lower system has iron or steel plate gi	
pedestrian hand rails are attractive lattices which duplicate the truss style	e.
10. DUOTOODADUS & SVETSU AAD ON DEVEDOS SIDE	
10. PHOTOGRAPHS & SKETCH MAP ON REVERSE SIDE. 11. RELATED SOURCES OF INFORMATION: HISTORICAL REFERENCES (PURLISHED ARTICLES, MANUSCRIPTS, DEPORTS, DRA	WINES PHOTO CPAPHIC BECORDS)
10. PHOTOGRAPHS & SKETCH MAP ON REVERSE SIDE. 11. RELATED SOURCES OF INFORMATION: HISTORICAL REFERENCES (PUBLISHED ARTICLES, MANUSCRIPTS, REPORTS, DRA' CONTACTS: (NAMES & ADDRESSES OF ANYONE WITH EYE-WITNESS ACCOUNTS OR RELEVANT INFORMATION); TAPE RE	
11. RELATED SOURCES OF INFORMATION: HISTORICAL REFERENCES (PUBLISHED ARTICLES, MANUSCRIPTS, REPORTS, DRA	
11. RELATED SOURCES OF INFORMATION: HISTORICAL REFERENCES (PUBLISHED ARTICLES, MANUSCRIPTS, REPORTS, DRA	
11. RELATED SOURCES OF INFORMATION: HISTORICAL REFERENCES (PUBLISHED ARTICLES, MANUSCRIPTS, REPORTS, DRA' CONTACTS: (NAMES & ADDRESSES OF ANYONE WITH EYE-WITNESS ACCOUNTS OR RELEVANT INFORMATION); TAPE RE	
11. RELATED SOURCES OF INFORMATION: HISTORICAL REFERENCES (PUBLISHED ARTICLES, MANUSCRIPTS, REPORTS, DRA' CONTACTS: (NAMES & ADDRESSES OF ANYONE WITH EYE-WITNESS ACCOUNTS OR RELEVANT INFORMATION); TAPE RE ESSEX Company Records - MVTM	ECORDINGS.
11. RELATED SOURCES OF INFORMATION: HISTORICAL REFERENCES (PUBLISHED ARTICLES, MANUSCRIPTS, REPORTS, DRA' CONTACTS: (NAMES & ADDRESSES OF ANYONE WITH EYE-WITNESS ACCOUNTS OR RELEVANT INFORMATION); TAPE RE	

.06



•	TO: Sally Z RETURN TO REVIEWER BY
	FROM: B.11 Sm. 44 (DATE)
	DATE: 7/5/86
	TOWN: LAWRENCE
	PROPERTY: L-4-3 Union St. over Merrimack River
	(NAME AND ADDRESS)
1	Does this property meet the criteria for NR eligibility?
1.	YES MHC- ely. Se 9/18/80
	□ NO
	A. Criteria
	a. events b. lives
	c. characteristics d. information
	B. Local State National -
•	
2.	Statement of Significance: OR Why not eligible?
	1888 - 5 SPAN DOUBLE INTERSECTION WARREN Through
	trus Gibest Known WARREN throis this in MHS.
	AND AN integral part both oviscally & Historically of
٠.	the mill evy of LAwrence
	Buil by Boston Bridge works
	DOE LEITER WRITTEN FILED IN ER FILE
, in the second	
	(DATE)

DETERMINATION OF ELIGIBILITY (MHC OPINION)

			·	
	TO: VKZ	<u> </u>	RETURN TO REVIEWER BY	
	FROM: phe	>	·	(DATE)
	DATE: 8.2	7 80		
	TOWN: LK	WRENCE		•
			lyion St. over Mernmache River	- Timick Bin
		AME AND ADDRESS)		
	D		. Nm . 1' '1'' 1'' 0	4
1.	Does this property me	et the criteria for	NK eligibility?	,
	<u></u>		Land language found	
	☐ NO		MHC Inventory form	•
	A. Criteria		missing from mo	
		events lives		
	c. (characteristics information		
	B. Local	State	National	
		ed breed ca		
2.	Statement of Signific	cance: OR Why not	t eligible?	
	Thin is al		averse the Merrimoure Rivers	•
	4	V	n 1858 complete with bridge pl	ates
	U U			
		الي:	: G.L. Vose: The bridge is type	
	of through truss	bridges being built	it at the time by a major h	ondaje
	building firm.	Its relative positi	ion will relation to other three	agh trus
•	bridge in his o	were connot at pr	exent be stated; however, "HEA	ed like to
			vioges across the Merrimacke be	
			indicate that this is an	
	umps tant =			
			בדובה זא בה הדום	
	DOE LETTER WRIT	T CIA	FILED IN ER FILE	

(DATE)

G-14-4

Fitch Bridge Rd. over Nashua River

1898 one span bridge is the third oldest of its type in the state. Built by the Berlin Iron Bridge Company, it is set in a picturesque wooded rural area. The bridge retains integrity with only minor alterations. Determined potentially eligible by the MHC November 23, 1982.

Lawrence

Groton

L-4-3

Union St. over Merrimack River

1888 five span bridge is the oldest known Warren through truss in Massachusetts and is an integral part both visually and historically of the mill city of Lawrence.

Montague

M-28-17

Eleventh St. over power canal

Rare 1916 three span bridge is a unique triple barreled Warren through truss. There is no upper lateral bracing on the center roadway section. This bridge may be one of a kind.

Worcester

W-44-140

Providence & Worcester R.R. over Southbridge St.

1910 one span Warren truss is an outstanding example of an unusual type of design.

The following bridge <u>does not</u> appear to be eligible for the National Register of Historic Places.

Boston

B-16-164

Babson St. over Amtrak R.R.

If you have any further questions, please feel free to contact William Smith at this office.

Sincerely,

Valerie A. Talmage Executive Director

State Historic Preservation Officer Massachusetts Historical Commission

cc: Mr. Robert McDonagh, MDPW c/o Mr. Frank Bracaglia

VAT/WS/dr



The Commonwealth of Massachusetts

Office of the Secretary of State Michael Joseph Connolly, Secretary

Massachusetts Historical Commission Valerie A. Talmage Executive Director State Historic Preservation Officer

January 6, 1987

Mr. James A. Walsh Division Administrator Federal Highway Administration Transportation Systems Center 55 Broadway - 10th Floor Cambridge, MA 02142

ATTN: Mr. H. Pearlman

RE: Warren Through Metal Bridges

Dear Mr. Walsh:

The Massachusetts Historical Commission staff has reviewed the historic bridge inventory forms prepared by the Massachusetts Department of Public Works. The MHC concurs with the preliminary findings of the MDPW that the following bridges appear to meet criteria for listing in the National Register of Historic Places.

Single-Intersection Warren Through Trusses

Florida/Rowe

F-5-1/R-10-5

Rowe RD over Deerfield River

1916 unaltered two span bridge is the third oldest of its type in the state. On an historic crossing leading to the former Hoosac Tunnel station on the B & M R.R., the bridge remains today in a very picturesque rural setting.

Holyoke

H-21-32

B & M R.R. over Lyman St.

1928 one span bridge is notable for its skew and sliding bearing in its approach span. Located within the Holyoke Canal System National Register Historic District.

Westfield

W-25-10

N. Elm St. over Westfield River

1938 two span with polygonal upper chords. Is in virtually untouched condition. Designed by Fay, Spofford & Thorndike.

The following bridges do not appear to be eligible for the National Register of Historic Places.

Athol

A-15-7

Exchange St. over Millers River

Boston

B-16-232

I-93 over Charles River

Cambridge

C-1-20

Alewife Brook Pkwy. over B & M R.R.

MHC determined not eligible January 30, 1981.

Fall River/Somerset

F-2-58/S-16-8

I-95 over Taunton River

MHC determined not eligible May 20, 1986.

Great Barrington

G-11-2

Division St. over Housatonic River

Great Barrington

G-11-8

Brookstone Rd. over Housatonic River

Lawrence

L-4-22

So. Union St. over B & M R.R.

Lee .

L-5-11

Center St. over Housatonic River

MHC determined not eligible July 7, 1980.

Ludlow/Wilbraham

L-16-3/W-35-1

Miller St. over Chicopee River

Malden

M-1-5

Mountain Ave. over MBTA

Northfield

N-22-14

East Northfield Rd. over B & M R.R.

Double-Intersection Warren Through Trusses

The following bridge was listed as a contributing element in the Turners Falls National Register Historic District May 10, 1982.

Montague

M-28-16

Sixth St. over power canal

The following bridges <u>appear</u> to be eligible for the National Register of Historic Places.

Buckland/Shelburne

B-28-22/S-11-1

Bridge St. over Deerfield River

1890 three span bridge is the second oldest Warren through truss in Massachusetts. Significant architectural details include latticed railing/portal bracing and builders plate. A visual landmark and an integral part of an historic village. Determined eligible by the Acting Keeper of the National Register December 17, 1981.

HAER No. MA-104

Duck Bridge (Union Street Bridge)
Spanning the Merrimack River on Union Street
Lawrence
Essex County
Massachusetts

PHOTOGRAPHS
WRITTEN HISTORICAL AND DESCRIPTIVE DATA

Historic American Engineering Record National Park Service Department of the Interior Washington, DC 20013-7127

HISTORIC AMERICAN ENGINEERING RECORD

DUCK BRIDGE (UNION STREET BRIDGE, LAWRENCE BRIDGE) HAER No. MA-104

Location:

Spanning the Merrimack River on Union Street, Lawrence,

Essex County, Massachusetts

UTM: Lawrence, Mass. Quad. 19/472999/3236100

Date of

Construction:

1888

Structural Type:

Five-span double-intersection Warren through truss bridge

Engineer:

George L. Vose, Consulting Engineer

Fabricator/

Builder:

Boston Bridge Works, Cambridge, Massachusetts

Previous Owner:

City of Lawrence, Massachusetts

Present Owner:

Massachusetts Department of Public Works, Boston

Use:

Vehicular and pedestrian bridge

Significance:

The Duck Bridge is the oldest double-intersection Warren through truss in the state under Massachusetts Department of Public Works purview, and is one of the state's oldest all-riveted bridges. It was built by a significant late-

nineteenth century bridge company, the Boston Bridge Works.

The bridge is an integral part, both visually and

historically, of the dramatic industrial landscape of the

City of Lawrence, Massachusetts.

Project

Information:

Documentation of the Duck Bridge is part of the

Massachusetts Historic Bridge Recording Project, conducted during the summer of 1990 under the co-sponsorship of HABS/HAER and the Massachusetts Department of Public Works, in cooperation with the Massachusetts Historical Commission.

John Healey, HAER Historian, August 1990

DUCK BRIDGE (UNION STREET BRIDGE/ LAWRENCE BRIDGE) HAER No. MA-104 (page 2)

Description

The Duck Bridge spans the Merrimack River close to the site of the Duck Mills. It connects the communities of Lawrence and South Lawrence at a point where both banks of the river are flanked by an extensive array of textile mills. The canals to the north and south are bridged nearby. These crossings have long been referred to as the Duck Bridge or Bridges. The main Duck Bridge, a five-span double-intersection Warren through truss, replaced an earlier timber bridge at this location in 1888.

The two bankside spans, utilizing the original piers (which have been raised) and abutments are 168'-8" long, and are subdivided into ten panels each. The three central spans are all 114'-0" in length, and are comprised of nine panels each. The panels in all the trusses measure 12'-8" in width. The overall height of the truss is 21'-74". The width across the center line of the chords is 31'-6", and the overall width including the two outrigger sidewalks is 49'-6". The trusses are of the double-intersection Warren pattern, a style sometimes called "lattice" in the nineteenth century.

The upper chord and inclined endposts are inverted troughs made of an 18" top plate and two 13½" side plates connected by continuous angles. A second plate is added to the top between the first and second panel points. The side plates are about 10½" apart. The bottoms of the side plates are connected with a single lattice, whose bars are bent at the ends for single rivet connections. The top chord is in four segments, connected by external splice plates. At the hip there is a short, bent plate on top and the side plates are connected by gusset plates, the inside ones being much larger because they also connect the web members. The inclined endposts, which slope at 60 degrees, are similar to the top chord, except that the side plates are ½" wider.

The lower chord is made of two inverted T sections, each comprised of a 13½" stem plate and two angles. In the shorter trusses, the segments are spliced by a pair of plates for the stem, and two angles plus a plate across the bottom for the chord angles. The stem plates of the bottom chords fit inside the side plates of the endposts and are riveted to them. The trusses rest on bearing plates, and are secured to them by small side clips. Nests of eight rollers are used at the expansion ends of the trusses.

The web compression members are made of two angles which toe out and are connected by double lacing bars. The tension members are also double angles, but these toe in and are connected by batten plates. The webs are riveted directly to the vertical plates of the chords; the outstanding legs of the compression members are connected to them by lug angles. The web members are connected where the tension member passes inside the angles of the one carrying compression. The compression angles range from 6"x4" to 3"x3", while the tension angles vary from 5"x3" to 3"x3".

The lateral bracing of the upper chord follows the Warren pattern. There are five panels in the longer trusses, each being equal in size to two panels of the main trusses. The shorter trusses have six panels, a bracing panel equals one-and-a-half main truss panels. The bracing members are comprised of two pairs of angles, $9\frac{1}{2}$ " back-to-back, connected with a single

DUCK BRIDGE (UNION STREET BRIDGE/ LAWRENCE BRIDGE) HAER No. MA-104 (page 3)

system of lacing bars. The portal bracing is a single Warren truss.

The transverse floor beams are built-up with a web plate and four angles, 3'-2½" deep at the trusses and 3'-6" deep at midspan. The beams are flush bottom with the lower chords and a horizontal plate connects them, as well as the lower chord bracing. The lower chord bracing is single angles, 4"x3", forming X's in every panel. The sidewalks are carried on trussed extensions to the floor beams. The railings are latticed, with cast iron rosettes, and the endposts are elaborate castings.²

Bridge Specifications

The committee in charge of the Duck Bridge chose Engineer George L. Vose of Boston "to prepare the general plan, and the specifications showing just what kind of bridge it was proposed to have."3 The specifications drawn up were most particular; the bridge was to have two spans of 123', and three spans of 110'-36/100"; the spans were to be of wrought-iron riveted lattice construction, with the trusses spaced 30' apart. The bridge was to be a through truss with "the roadway resting on the lower chords," and a clear headroom of 15'. The weight of each span was around 200 tons. Of the materials used in the bridge "all wrought iron is to be tough fibrous, uniform in quality, free from blisters, flaws or other imperfections." It was to have an ultimate tensile strength of 46,000 lbs./sq.in., and an elastic limit of not less than 23,000 lbs./sq.in., while no iron less than 4" was to be used in the structure. The bridge was to be built to carry "a general load of 80 lbs./sq.ft. on any part of the roadway or sidewalks." Vose suggested that such a load was "hardly possible ... except by packing a mass of picked men all over the bridge as close as they can stand." A considerable safety factor appears to have been built into the design as Vose continues "this load is only one fifth part of that which would break the bridge down." The floor was to carry "a concentrated load of 16 tons on 4 wheel." At these loads the members were to be proportioned and arranged so that "the maximum strains must not exceed 10,000 lbs./sq.in. of the net section for general tension members." Compression members were to be proportioned according to an empirical formula relating length and cross-section to a maximum permitted strain. Members "subject to alternate strains of tension and compression" were to be "proportioned to resist both strains." The lateral bracing system was to be "proportioned for a wind pressure of 30 lbs./sq.ft." Portal bracing was to be installed, and be "capable of carrying the upper wind strains to the abutments." Specifications for the proportioning of compression members, and of riveting pitch, shearing and bearing capacity are included, together with numerous other matters of detail. References in the text suggest that the specifications were accompanied by plans drafted by Vose.4

Boston Bridge Works

Boston Bridge Works evolved from the failed National Bridge & Iron Works of Boston. David Andrews, one-time employee of the now bankrupt concern, bought the plant of his erstwhile employers in 1876. He did not, however, use

DUCK BRIDGE (UNION STREET BRIDGE/ LAWRENCE BRIDGE) HAER No. MA-104 (page 4)

their East Boston shops, moving the equipment to a new location in Cambridge. Initially trading under the proprietor's own name, the company became known as the Boston Bridge Works in 1879. Andrews had received both a practical engineering machine shop apprenticeship and a measure of formal engineering training at Dartmouth College. During the early 1870s he was employed by C.H. Parker at National Bridge, where he distinguished himself in design work for that company. He was particularly noted for his innovative approach to the design of Boston's Union Station. It is unclear whether Andrews was in National Bridge's employ at the time of their bankruptcy.

Andrews does not appear to have continued production of National Bridge's stock product, the Parker Patent Truss. It appears that from an early date he made a decision to specialize in bridges of Warren or Pratt configuration. The company's oldest surviving bridge, constructed in 1878, located on Main Street in Framingham, Massachusetts, is an all-riveted Warren truss, though its bowstring chord is perhaps a vestige of National Bridge shop practice.

By the mid 1880s the company had sufficient financial security to expand their capacity to 5,000 tons. The company's reputation for efficient production and competent workmanship impressed George Vose, who had implored the City of Lawrence to be "mindful to the character of the builder, [and] to the style of his work."

Earlier Bridges at Lawrence

The City of Lawrence developed rapidly following the formation of the Essex Company in 1845. The company was founded by a group of Boston businessmen, keen to emulate the success of Lowell. To this end they impounded the waters of the Merrimack River behind the Great Dam, and built to the north and south of the river two parallel power canals. The provision of water power supplied the catalyst for the rapid development of a thriving textile industry, that was to provide the economic base upon which the city was founded.

Prior to this period the banks of the river were bound by the townships of Andover, to the south, and Methuen to the north. The two were first connected by a bridge in 1793. In that year the "proprietors of Andover Bridge" were given powers to construct a crossing and charge tolls for its use. The timber structure was completed by November of that year, and occupied the site of the present railroad bridge. In common with many of its contemporaries it was rebuilt many times, and relocated at the site of the present O'Leary Bridge.

In 1854 George Davis and George Cabot were incorporated as the proprietors of Lawrence Bridge. In that year an Act (Chapter 265) was passed allowing them to build a new toll bridge to span the river at the eastern end of the Lawrence. For some reason, the authorization to construct this bridge was turned over to the county, and during October of that same year, the Essex County Commissioners laid out Union Street "to the southerly edge of said bridge." The bridge was constructed between 1854 and 1855. Its four covered, lattice timber spans rested on stone abutments and piers. The three piers of

DUCK BRIDGE (UNION STREET BRIDGE/ LAWRENCE BRIDGE) HAER No. MA-104 (page 5)

the bridge were to be built by a contractor under the direction of the Essex Company's engineer. The piers were to be founded on the natural bed of the river, and protected from scour by loose stones placed around their base. The structure was 612' long and 40' wide, and was said to have cost about \$50,000. Under an Act of 1868 (Chapter 299) the County Commissioners laid out Lawrence Bridge as a public highway, charging the city with the structure's maintenance.

During the years 1885 and 1886 the following works were undertaken: the deck was replanked, the suspension trusses repaired, and minor works undertaken on the walkways and rails. It was proposed that "a pitched roof should be built on the road guard instead of the present flat one."9 However, the condition of the bridge seems to have been a matter of local concern. Although it had been repeatedly examined and pronounced safe, it was said to have been unsafe for years and was considered "a structure of known weakness admitted to be dangerous." 10

On May 4, 1887, the Merrimack was reported to be spanned by "an arch of flames." A fire broke out on Duck Bridge during the afternoon of that day. At 5:45 p.m. "a small wreathe of smoke" was noted coming from the roadway at the first pier from the south abutment. Within minutes it was reported that "a mass of flames shot up from the west coping [of the pier]." Fanned by a northwesterly wind the whole southern section was reported to be "a seething mass of flames [and] a solid barrier of fire nearly 100' high." By 6:00 p.m. only two spans remained standing and the fire was spreading across them, "the boards [of the housing] falling off to reveal the burning lattice work." By 6:17 the remaining spans fell. City and mill fire brigades were in early attendance. 12

The City Council acted promptly to replace the structure. On the day following the fire a Special Committee was appointed and authorized to: "procure plans and estimate for rebuilding the bridge, ... employ experts and engineers, ... [and] consider the expediency of building a temporary bridge." The Mayor was authorized to petition the Legislature for authority to issue bonds not to exceed \$75,000 to pay for a new bridge. Under Chapter 299 of the Acts of 1887 such authority was granted. The old bridge said to have been worth \$28,000, but the structure was not insured.

A temporary trestle bridge was built on the piles driven 3' into the river bed. Misfortune seems to have befallen the city during the early summer of 1887, for on June 24, 1887, storm waters broke the log booms at Lowell and Chelmsford Dams. A "100-log drive" swept over Lawrence Dam and became trapped beneath the temporary bridge. As the waters rose the bridge was lifted and half of it swept away. Remarkably the wayward half was recovered from Newburyport to be towed upstream and reinstated! 13

George L. Vose

The Committee appointed George L. Vose as consulting engineer to the City. Vose appears to have been something of a crusading figure in the business of bridge contracting. As Professor of Civil Engineering at Massachusetts Institute of Technology he corresponded in strong terms

DUCK BRIDGE (UNION STREET BRIDGE/ LAWRENCE BRIDGE) HAER No. MA-104 (page 6)

concerning the Aiken Street Bridge (HAER No. MA-106) contract in the neighboring city of Lowell. He advised the Mayor of Lawrence against the "false idea of economy" that might risk "disaster." He warned the Mayor of "the many companies" who would build a bridge according to the town's budget, with the consequence that "there are hundreds of bridges ... which await only some extra heavy load ... to break down." It was his intention to ensure that Lawrence was provided with a bridge "that will certainly be safe under all possible conditions." Recalling Lowell's experience over the Aiken Street Bridge contract, Vose advised the Bridge Committee that in order to "avoid such a fizzle as that here" they should deal with "safe, reliable companies, they who take pride in their work, and who transact their business on a firm basis." Vose advised the city against indiscriminate letting of the contract. He suggested that instead of following the the usual practice of "advertizing for proposals, and allowing all sorts of companies good bad and indifferent to send allsorts of plans at all sorts of prices" he should "prepare a general plan, and the specifications, showing just what kind of bridge it was proposed to have." He proposed to submit his plans to only "half a dozen of the most reliable companies" who would bid "a fair price for doing the work." 14

Construction of Duck Bridge

The Special Bridge Committee heeded Vose's advice. Vose, in consultation with City Engineer Marble, devised plans and asked six bridge companies to bid on them. It was decided to shorten the central spans of the bridges, rendering the central pier redundant. It was agreed to build two new piers to either side ofthe center of the river, and to rebuild the new bankside piers and the abutments to a higher level to accept the new iron superstructure. It was to be the responsibility of the City Engineer to oversee this work. The bridge design was to be a latticed wrought iron truss. (Presumably Vose's plan depicted the form now classified as a double-intersection Warren truss.)

At the Special Bridge Committee meeting of June 27, 1887, Vose informed those present of the replies he had received from the six companies from whom he had requested bids: the Union Bridge Company of New York could not build the bridge that season; the Keystone Bridge Company of Pittsburgh was too busy to build in the time required; the Philadelphia Bridge Company did not build highway bridges at that time of the year, and in any case, could not do so that season; the Rochester Bridge Company quoted the lowest price of \$35,000, but stated that they could not complete in the time required; the Boston Bridge Works furnished the next lowest bid at \$39,790, but would not be able to finish until February of the following year; the Niagara Company of Buffalo quoted a price of \$44,650, for completion by the end of the year. At the same meeting it was resolved that "there forthwith be built by contract an iron bridge." Having considered the bids the Committee met on July 27, 1887, to award the contracts for the ironwork. It was moved and accepted that the Boston Bridge Company be awarded the contract, that the bridge completed by February 1, 1888, and that a penalty of \$50 per day be imposed for any delay. The contract was signed by D.H. Andrews on August 6, 1887, although the

DUCK BRIDGE (UNION STREET BRIDGE/ LAWRENCE BRIDGE) HAER No. MA-104 (page 7)

penalty clause was excluded. 15

While the arrangements for the ironwork were being finalized, the bids for the masonry work were considered. At a meeting of the Special Bridge Committee on July 12, 1887, the contract was awarded to local contractors Trumball, Cheney, Moulton & O'Mahoney, who bid \$14,737. Although a lower bid of \$13,826 was received, it was rejected on the basis of it being made "for a Boston firm." Two other companies tendered bids of \$15,323 and \$15,798. The successful company calculated their offer on the basis of the following costings: cut stone granite masonry \$24.50; rubble masonry \$5.75; rip-rap (loose stone at the foot of the structure) 75¢. The contract called for the construction of of two new piers. As the river bed was composed of compacted boulders and gravel pile driving was not possible and the piers were to be founded on a rubble stone foundation, excavated 1' into the river bed. Of the three old piers, the middle one was to be removed and the stone used in the new works, while the remaining two were to be extended at nose and tail, and built up to the elevation of the new bridge. Likewise the old abutments were to be raised and widened. Coursed granite cutwaters were to be built on the upstream face of the piers. The piers were to be capped by dressing copings. Elsewhere rubble masonry was to suffice. The successful company was expected to complete the work within twelve weeks, the structure being ready to receive the ironwork by October 4, 1887. A penalty of \$25 per day was to be imposed for any delay. 16

Details of the bridge's construction are slight, although the completion of the masonry work appears to have been considerably delayed. The old piers seem to have required much attention, the City Engineer speaking of the "four new piers" in his report on the bridge. ¹⁷ It was not until mid-December that the masonry was reported to have been completed. By this date an extension railway had been built to the southern end of the bridge works, and it was reported that "seven car loads of lumber, to be used in the staging has arrived from the iron works, but the iron is not expected before February." Upon arrival it was to be "put-up in about four weeks ... if river conditions were favorable." 18 It would seem that while awaiting the arrival of the ironwork the bridge builders were busy erecting the falsework (staging) on which the ironwork would be assembled. Progress must have been interrupted, when on January 8, 1888, a freight train carrying timber suffered brake failure, and two cars fell into the river while a third was left hanging from the abutment. 19 It is not recorded when bridge erection began, however the bridge works promised the City that material would arrive at the site to allow construction to commence before January 15, 1888.20 The bridge would appear to have been substantially complete by March 15, 1888, when the trusses were being painted. On this date, D.H. Andrews advised the city that the bridge might be "opened to travel on the following Saturday."21

On March 24, 1888, Vose made his final inspection of the bridge, expressing his satisfaction he recommended the City to make final payments to Boston Bridge Works. City Engineer Marble pronounced his satisfaction with the completed bridge, having checked the dimensions of all members, and carried out a load test of March 30, 1888. A deflection of % was noted as "three double dump carts loaded with gravel, passing three abreast across the

DUCK BRIDGE (UNION STREET BRIDGE/ LAWRENCE BRIDGE) HAER No. MA-104 (page 8)

the bridge." The test load was said to be 83½ tons. 23 Vose in his correspondence of March 24, 1888, had suggested that little was to be gained by such tests. He advised the Mayor that "for a test to be meaningful its effect must be known, particularly has any part been overstrained by loading during testing" he reaffirmed his conviction that the "best test of quality was computation from plans, and the character of the builder."

The final account for the bridge amounted to \$64,220.22. Boston Bridge Works received \$39,790 in three payments. The masonry contractor received \$18,534.09, the total cost of the masonry amounting to \$21,712.31 including materials and superintendence. Vose received his usual fee of 1 percent of the bridge contractor's fee. The Essex Bridge Company received a nominal payment for the additional obstruction to river flow caused by the additional pier. Essex County Commissioners, under the authority of the Chapter 106 of the Acts of 1888, were empowered to reimburse the city for 25 percent of their expenditure on the bridge. The county contribution became a matter for contoversy for a short time, Essex refusing to make payment as in their haste to rebuild the bridge the City had omitted to consult with the County over their plans. This diplomatic oversight was however soon forgotten and the payment made. Those monies provided by the City were raised by \$2,000 and \$1,000 yielding 4 percent over their fifteen-year term. 24

As part of the overall improvements to Union Street it was considered opportune to renew the adjacent North and South Canal Bridges as part of the main river crossing project. To this end, Boston Bridge Works provided a Warren truss and a plate girder bridge for the North and South Canals respectively. The Moseley iron bridge over the South Canal was relocated to carry Parker Street over the South Canal. The main bridge has only required the usual renewal of decking in the ensuing years. In 1914 both stringers and deck were renewed, the shelf brackets being upgraded at this time. In 1939 the wooden deck system was replaced in steel employing I-beam stringers and a steel grid deck. In 1910 the bridge was transferred to the authority of Essex County, who passed it to the state on January 1, 1966.

DUCK BRIDGE (UNION STREET BRIDGE/ LAWRENCE BRIDGE) HAER No. MA-104 (page 9)

ENDNOTES

- 1. Original plans for Duck Bridge, 1887, located at the Office of the City Engineer, Lawrence, Massachusetts.
- 2. Ibid., "Details of Floor."
- 3. Letter from Vose to Mayor Mack, March 24, 1888. The letter explains at great length the process by which the City contracted for the bridge. Located in the files of the City Engineer, Lawrence City Hall.
- 4. Original plans and specifications for Duck Bridge, 1887; and, Letter from Vose to Mayor Mack, March 24, 1888.
- 5. Vose to Mayor Mack, March 24, 1888.
- 6. Specifications for Duck Bridge piers, 1855. Located in the files of the City Engineer, Lawrence City Hall.
- 7. <u>Lawrence American</u>, May 6, 1887.
- 8. "Lawrence up to Date, 1845-1895."
- 9. Report of Superintendent of Public Property, Lawrence City Book 1886-87.
- 10. "The Lawrence American Congratulates Itself on the Burning of Duck Bridge," <u>Lawrence American</u>, May 10, 1887.
- 11. "Gone at Last Report of Destruction of Duck Bridge," <u>Lawrence American</u>, May 6, 1887.
- 12. Ibid.
- 13. <u>Lawrence American</u>, July 1, 1887; and, City Engineer's Report, <u>Lawrence City Books 1887-88</u>, p. 26.
- 14. Lawrence American, July 1, 1887; and, Letter from Vose to Mayor Mack.
- 15. <u>Lawrence American</u>, July 1 and 22, 1887. The original contract between Boston Bridge Works and the City is located at the City Engineer's Office, Lawrence City Hall.
- 16. Lawrence American, July 15, 1887.
- 17. City Engineer's Report, Lawrence City Book 1887-88, p. 27.

DUCK BRIDGE (UNION STREET BRIDGE/ LAWRENCE BRIDGE) HAER No. MA-104 (page 10)

- 18. "The New Bridge," Lawrence American, December 16, 1887.
- 19. Lawrence American, January 13, 1888.
- 20. Mayor's Address, Lawrence City Book 1887-88, p. 19.
- 21. Letter from Andrews to Mayor Mack, March 15, 1888.
- 22. Vose to Mayor Mack, March 24, 1888.
- 23. Letter from Marble to Mayor Mack, April 13, 1888.
- 24. <u>Lawrence City Books 1887-88</u>, pp. 23, 28 and 56; and <u>1888-89</u>, pp. 293-94.

DUCK BRIDGE (UNION STREET BRIDGE/ LAWRENCE BRIDGE) HAER No. MA-104 (page 11)

BIBLIOGRAPHY

Duck Bridge files, located in the Office of the City Engineer, Lawrence City Hall.

Lawrence American, Lawrence, Massachusetts, 1887-88.

Lawrence City Book, 1886-87 and 1887-88.

"Lawrence Up To Date, 1845-1895."

Original plans for Duck Bridge, 1887, located in the Office of the City Engineer, Lawrence City Hall.

HISTORIC AMERICAN ENGINEERING RECORD

INDEX TO PHOTOGRAPHS

Duck Bridge (Union Street Bridge)
Spanning the Merrimack River on Union Street
Lawrence
Essex County
Massachusetts

HAER No. MA-104

Martin Stupich, Photographer, Summer 1990

MA-104-1	General view from north river bank, looking southeast
MA-104-2	General view from north river bank, showing two northern spans, looking east
MA-104-3	Oblique view from north river bank, showing central and southern spans, looking southeast
MA-104-4	General view of north portal from roadway, looking south
MA-104-5	Elevation of north portal from roadway, looking south
MA-104-6	Elevation of north portal from roadway, looking south
MA-104-7	Detail of north truss from roadway, showing truss geometry, looking southwest
MA-104-8	Detail of north truss from roadway, showing truss geometry and connections, looking northeast
MA-104-9	Detail of builder's plate on northwest endpost, looking southeast
MA-104-10	Detail of west pedestrian walkway with windbreak, from north portal end, looking south
MA-104-11	Detail of east pedestrian walkway with railing, from north portal end, looking south
MA-104-12	Detail of underside of deck from south river bank, looking north
MA-104-13	Detail of masonry pier, looking north
MA-104-14	Detail of bearing shoe connections at south abutment, looking southeast





