The National Bridge Inventory contains data submitted by state transportion departments to the Federal Highway Administration in coded format.

Form Interface Design: www.historicbridges.org. Data Conversion Assistance By www.bridgehunter.com. None of the involved parties make any guarantee of accuracy.

Basic Information							42-14-37 =	086-00-40 = -
Michigan [26]	Aichigan [26] Van Buren County [159]		Lawrence [46460] 0.2 MI E OF 48TH STREE		STREET	42-14-37 = 42.243611		86.011111
80303H00004B010 Highway agency district 5		Owner County Highwa	Owner County Highway Agency [02] Maintenance responsibility		County Highway Agency [02]			
Route 0 48TH AVE		Toll On fr	Toll On free road [3] Features intersected PAW PAW		RIVER			
Design - Main Steel [3] Stringer/Mu	llti-beam or girder [02]	Design - approach Other	- [00]	Kilometerpoint Year built 1930 Skew angle 0 Historical significa	Structure F	constructed N/A		
Total length 27.7 m = 90.9 ft Length of maximum span 13.7 m = 44.9 ft Deck width, out-to-out 8.6 m = 28.2 ft Bridge roadway width, curb-to-curb 6.7 m = 22.0 ft								
Inventory Route, Total Horizontal Clearance 6.7 m = 22.0 ft		Curb or sidewalk v	Curb or sidewalk width - left 0.4 m = 1.3 ft Curb or side		ewalk width - right	0.4 m = 1.3 ft		
Deck structure type	Со	oncrete Cast-in-Pla	ce [1]					
Type of wearing surface Bituminous [6]								
Deck protection								
Type of membrane/we	earing surface							
Weight Limits								
Bypass, detour length Method to determine inventory rating			Load Factor(LF) [1]		Inventory rating	23.6 metric ton	= 26.0 tons	
0.3 km = 0.2 mi Method to determine operating rating			Load Factor(LF) [1]		Operating rating	39.4 metric ton	= 43.3 tons	
Bridge posting 20.0 - 29.9 % below [2]					Design Load			

Functional Details								
Average Daily Traffic 700 Average daily tr	uck traffi 0 % Year 2003 Future average daily traffic 1000 Year 2023							
Road classification Local (Rural) [09]	Lanes on structure 2 Approach roadway width 10.1 m = 33.1 ft							
Type of service on bridge Highway [1]	Direction of traffic 2 - way traffic [2] Bridge median							
Parallel structure designation No parallel structure exists. [N]								
Type of service under bridge Waterway [5]	Lanes under structure 0 Navigation control							
Navigation vertical clearance 0 = N/A Navigation horizontal clearance 0 = N/A								
Minimum navigation vertical clearance, vertical lift bridge Minimum vertical clearance over bridge roadway 99.99 m = 328.1 ft								
Minimum lateral underclearance reference feature Feature not a highway or railroad [N]								
Minimum lateral underclearance on right 99.9 = Unlimited Minimum lateral underclearance on left 0 = N/A								
Minimum Vertical Underclearance 0 = N/A Minimum vertical underclearance reference feature Feature not a highway or railroad [N]								
Appraisal ratings - underclearances N/A [N]								
Repair and Replacement Plans								
Type of work to be performed	Work done by Work to be done by contract [1]							
Replacement of bridge or other structure because of substandard load carrying capacity or substantial	Bridge improvement cost 480000 Roadway improvement cost 150000							
bridge roadway geometry. [31]	Length of structure improvement 33.5 m = 109.9 ft Total project cost 630000							
	Year of improvement cost estimate 2003							
	Border bridge - state Border bridge - percent responsibility of other state							
	Border bridge - structure number							

Inspection and Sufficiency								
Structure status Posted for lo	ad [P]	Appraisal ratings - structural	Equal to present minimum criteria [6]					
Condition ratings - superstructur Satisfactory [6]		Appraisal ratings - roadway alignment	Equal to present desirable criteria [8]					
Condition ratings - substructure	Satisfactory [6]	Appraisal ratings -	Meets minimum tolerable limits to be left in place as is [4]					
Condition ratings - deck	Satisfactory [6]	deck geometry						
Scour	Bridge foundation	Bridge foundations determined to be stable for the assessed or calculated scour condition. [8]						
Channel and channel protection		Bank is beginning to slump. River control devices and embankment protection have widespread minor damage. There is minor stream bed movement evident. Debris is restricting the channel slightly. [6]						
Appraisal ratings - water adequac	Better than preso	ent minimum criteria [7]	Status evaluation					
Pier or abutment protection			Sufficiency rating 74.4					
Culverts Not applicable. Used	if structure is not a culve	rt. [N]						
Traffic safety features - railings								
Traffic safety features - transition	ns	npected feature meets currently acce	eptable standards. [1]					
Traffic safety features - approach	n guardrail	inpected feature meets currently acce	eptable standards. [1]					
Traffic safety features - approach	n guardrail ends	inpected feature meets currently acce	eptable standards. [1]					
Inspection date September 2009 [0909] Designated inspection frequency 12 Months								
Underwater inspection	Not needed [N]	Underwater inspec	ction date					
Fracture critical inspection	Not needed [N]	Fracture critical in:	Fracture critical inspection date					
Other special inspection	Not needed [N]	Other special insp	pection date					