

HistoricBridges.org - National Bridge Inventory Data Sheet

2021 Inventory

The National Bridge Inventory contains data submitted by state transportation departments to the Federal Highway Administration in coded format.

Form Interface Design: www.historicbridges.org. Data Conversion Assistance By www.bridgehunter.com. None of the involved parties make any guarantee of accuracy.

Basic Information

Michigan [26]	Wayne County [163]	Dearborn [21000]	IN DEARBORN	42-19-35.81 = 42.326614	083-09-38.17 = -83.160603
11140	Highway agency district: 7	Owner State Highway Agency [01]	Maintenance responsibility	State Highway Agency [01]	
Route 12		US-12 (MICHIGAN AV	Toll On free road [3]	Features intersected I-94	
Design - main	Steel [3]	Design - approach		Kilometerpoint 265.7 km = 164.7 mi	
2	Stringer/Multi-beam or girder [02]	0	Other [00]	Year built 1948	Year reconstructed 1996
				Skew angle 55	Structure Flared
				Historical significance	Bridge is on the NRHP. [1]
Total length	68.2 m = 223.8 ft	Length of maximum span	36.3 m = 119.1 ft	Deck width, out-to-out	35.9 m = 117.8 ft
Inventory Route, Total Horizontal Clearance	30.4 m = 99.7 ft	Curb or sidewalk width - left	3.8 m = 12.5 ft	Curb or sidewalk width - right	2.4 m = 7.9 ft
Deck structure type	Concrete Cast-in-Place [1]				
Type of wearing surface	Monolithic Concrete (concurrently placed with structural deck) [1]				
Deck protection	Epoxy Coated Reinforcing [1]				
Type of membrane/wearing surface					

Weight Limits

Bypass, detour length	Method to determine inventory rating	Load Factor (LF) rating reported by rati	Inventory rating	52.8 metric ton = 58.1 tons
0 km = 0.0 mi	Method to determine operating rating	Load Factor (LF) rating reported by rati	Operating rating	88.1 metric ton = 96.9 tons
Bridge posting	Equal to or above legal loads [5]	Design Load	MS 18 / HS 20 [5]	

Functional Details

Average Daily Traffic	28335	Average daily truck traffi	4	%	Year	2007	Future average daily traffic	12250	Year	2026
Road classification	Other Principal Arterial (Urban) [14]		Lanes on structure	9		Approach roadway width	27.4 m = 89.9 ft			
Type of service on bridge	Highway-pedestrian [5]		Direction of traffic	2 - way traffic [2]		Bridge median				
Parallel structure designation	No parallel structure exists. [N]									
Type of service under bridge	Highway, with or without ped		Lanes under structure	6		Navigation control	Not applicable, no waterway. [N]			
Navigation vertical clearanc	0 = N/A		Navigation horizontal clearance	0 = N/A						
Minimum navigation vertical clearance, vertical lift bridge						Minimum vertical clearance over bridge roadway	99.99 m = 328.1 ft			
Minimum lateral underclearance reference feature	Highway beneath structure [H]									
Minimum lateral underclearance on right	27 m = 88.6 ft					Minimum lateral underclearance on left	1.8 m = 5.9 ft			
Minimum Vertical Underclearance	4.42 m = 14.5 ft		Minimum vertical underclearance reference feature	Highway beneath structure [H]						
Appraisal ratings - underclearances	Basically intolerable requiring high priority of corrective action [3]									

Repair and Replacement Plans

Type of work to be performed

Work done by

Bridge improvement cost

Roadway improvement cost

Length of structure improvement

Total project cost

Year of improvement cost estimate

Border bridge - state

Border bridge - percent responsibility of other state

Border bridge - structure number

Inspection and Sufficiency

Structure status	Open, no restriction [A]	Appraisal ratings - structural	Equal to present minimum criteria [6]
Condition ratings - superstructure	Satisfactory [6]	Appraisal ratings - roadway alignment	Equal to present desirable criteria [8]
Condition ratings - substructure	Satisfactory [6]	Appraisal ratings - deck geometry	Basically intolerable requiring high priority of replacement [2]
Condition ratings - deck	Good [7]		
Scour	Bridge not over waterway. [N]		
Channel and channel protection	Not applicable. [N]		
Appraisal ratings - water adequacy	N/A [N]	Status evaluation	
Pier or abutment protection		Sufficiency rating	
Culverts	Not applicable. Used if structure is not a culvert. [N]		
Traffic safety features - railings	Inspected feature meets currently acceptable standards. [1]		
Traffic safety features - transitions	Inspected feature meets currently acceptable standards. [1]		
Traffic safety features - approach guardrail	Inspected feature meets currently acceptable standards. [1]		
Traffic safety features - approach guardrail ends	Inspected feature meets currently acceptable standards. [1]		
Inspection date	September 1999 [999]	Designated inspection frequency	24 Months
Underwater inspection	Not needed [N]	Underwater inspection date	
Fracture critical inspection	Not needed [N]	Fracture critical inspection date	
Other special inspection	Not needed [N]	Other special inspection date	

HistoricBridges.org - National Bridge Inventory Data Sheet

2021 Inventory

The National Bridge Inventory contains data submitted by state transportation departments to the Federal Highway Administration in coded format.

Form Interface Design: www.historicbridges.org. Data Conversion Assistance By www.bridgehunter.com. None of the involved parties make any guarantee of accuracy.

Basic Information

Michigan [26]	Wayne County [163]	Dearborn [21000]	IN DEARBORN	42-19-34.47 = 42.326242	083-09-42.89 = -83.161914
11139	Highway agency district: 7	Owner State Highway Agency [01]	Maintenance responsibility	State Highway Agency [01]	
Route 12		US-12 (MICHIGAN AV	Toll On free road [3]	Features intersected I-94 RAMP	
Design - main	Steel [3]	Design - approach		Kilometerpoint 254.1 km = 157.5 mi	
1	Stringer/Multi-beam or girder [02]	0	Other [00]	Year built 1944	Year reconstructed 1968
				Skew angle 19	Structure Flared
				Historical significance	Bridge is on the NRHP. [1]
Total length	15.2 m = 49.9 ft	Length of maximum span	15.2 m = 49.9 ft	Deck width, out-to-out	35.9 m = 117.8 ft
Inventory Route, Total Horizontal Clearance	30.4 m = 99.7 ft	Curb or sidewalk width - left	3.9 m = 12.8 ft	Curb or sidewalk width - right	3.9 m = 12.8 ft
Deck structure type	Concrete Cast-in-Place [1]				
Type of wearing surface	Latex Concrete or similar additive [3]				
Deck protection					
Type of membrane/wearing surface					

Weight Limits

Bypass, detour length	Method to determine inventory rating	Load Factor (LF) rating reported by rati	Inventory rating	37.3 metric ton = 41.0 tons
0 km = 0.0 mi	Method to determine operating rating	Load Factor (LF) rating reported by rati	Operating rating	62.2 metric ton = 68.4 tons
	Bridge posting	Equal to or above legal loads [5]	Design Load	MS 18 / HS 20 [5]

Functional Details

Average Daily Traffic	28335	Average daily truck traffi	5	%	Year	2007	Future average daily traffic	31582	Year	2018
Road classification	Other Principal Arterial (Urban) [14]		Lanes on structure	9		Approach roadway width	27.4 m = 89.9 ft			
Type of service on bridge	Highway-pedestrian [5]		Direction of traffic	2 - way traffic [2]		Bridge median				
Parallel structure designation	No parallel structure exists. [N]									
Type of service under bridge	Highway, with or without ped		Lanes under structure	2		Navigation control	Not applicable, no waterway. [N]			
Navigation vertical clearanc	0 = N/A		Navigation horizontal clearance	0 = N/A						
Minimum navigation vertical clearance, vertical lift bridge						Minimum vertical clearance over bridge roadway	99.99 m = 328.1 ft			
Minimum lateral underclearance reference feature	Highway beneath structure [H]									
Minimum lateral underclearance on right	29 m = 95.1 ft					Minimum lateral underclearance on left	3 m = 9.8 ft			
Minimum Vertical Underclearance	4.5 m = 14.8 ft		Minimum vertical underclearance reference feature	Highway beneath structure [H]						
Appraisal ratings - underclearances	Basically intolerable requiring high priority of corrective action [3]									

Repair and Replacement Plans

Type of work to be performed	Work done by	Work to be done by contract [1]		
Bridge deck replacement with only incidental widening. [37]	Bridge improvement cost	45000	Roadway improvement cost	
	Length of structure improvement		Total project cost	
	Year of improvement cost estimate			
	Border bridge - state		Border bridge - percent responsibility of other state	
	Border bridge - structure number			

Inspection and Sufficiency

Structure status	Open, no restriction [A]	Appraisal ratings - structural	Equal to present minimum criteria [6]
Condition ratings - superstructure	Good [7]	Appraisal ratings - roadway alignment	Better than present minimum criteria [7]
Condition ratings - substructure	Satisfactory [6]	Appraisal ratings - deck geometry	Basically intolerable requiring high priority of replacement [2]
Condition ratings - deck	Good [7]		
Scour	Bridge not over waterway. [N]		
Channel and channel protection	Not applicable. [N]		
Appraisal ratings - water adequacy	N/A [N]	Status evaluation	
Pier or abutment protection		Sufficiency rating	
Culverts	Not applicable. Used if structure is not a culvert. [N]		
Traffic safety features - railings	Inspected feature meets currently acceptable standards. [1]		
Traffic safety features - transitions	Not applicable or a safety feature is not required. [N]		
Traffic safety features - approach guardrail	Not applicable or a safety feature is not required. [N]		
Traffic safety features - approach guardrail ends	Not applicable or a safety feature is not required. [N]		
Inspection date	September 1999 [999]	Designated inspection frequency	24 Months
Underwater inspection	Not needed [N]	Underwater inspection date	
Fracture critical inspection	Not needed [N]	Fracture critical inspection date	
Other special inspection	Not needed [N]	Other special inspection date	

HistoricBridges.org - National Bridge Inventory Data Sheet

2021 Inventory

The National Bridge Inventory contains data submitted by state transportation departments to the Federal Highway Administration in coded format.

Form Interface Design: www.historicbridges.org. Data Conversion Assistance By www.bridgehunter.com. None of the involved parties make any guarantee of accuracy.

Basic Information

Michigan [26]	Wayne County [163]	Dearborn [21000]	IN DEARBORN	42-19-39.41 = 42.327614	083-09-33.88 = -83.159411
11141	Highway agency district: 7	Owner State Highway Agency [01]	Maintenance responsibility	State Highway Agency [01]	
Route 12		RAMP TO US-12	Toll On free road [3]	Features intersected I-94	
Design - main	Steel [3]	Design - approach		Kilometerpoint 8.2 km = 5.1 mi	
2	Stringer/Multi-beam or girder [02]	0	Other [00]	Year built 1948	Year reconstructed N/A [0000]
				Skew angle 15	Structure Flared
				Historical significance	Bridge is not eligible for the NRHP. [5]
Total length	35.3 m = 115.8 ft	Length of maximum span	17.6 m = 57.7 ft	Deck width, out-to-out	13.9 m = 45.6 ft
				Bridge roadway width, curb-to-curb	13.4 m = 44.0 ft
Inventory Route, Total Horizontal Clearance	13.4 m = 44.0 ft	Curb or sidewalk width - left	0 m = 0.0 ft	Curb or sidewalk width - right	0 m = 0.0 ft
Deck structure type	Concrete Cast-in-Place [1]				
Type of wearing surface	Latex Concrete or similar additive [3]				
Deck protection					
Type of membrane/wearing surface					

Weight Limits

Bypass, detour length	Method to determine inventory rating	Load Factor (LF) rating reported by rati	Inventory rating	41.5 metric ton = 45.7 tons
0 km = 0.0 mi	Method to determine operating rating	Load Factor (LF) rating reported by rati	Operating rating	69.3 metric ton = 76.2 tons
	Bridge posting	Equal to or above legal loads [5]	Design Load	MS 18 / HS 20 [5]

Functional Details

Average Daily Traffic	11760	Average daily truck traffi	0	%	Year	1982	Future average daily traffic	13524	Year	2002
Road classification	Other Principal Arterial (Urban) [14]		Lanes on structure	2		Approach roadway width	12.2 m = 40.0 ft			
Type of service on bridge	Highway [1]		Direction of traffic	1 - way traffic [1]		Bridge median				
Parallel structure designation	No parallel structure exists. [N]									
Type of service under bridge	Highway, with or without ped		Lanes under structure	6		Navigation control	Not applicable, no waterway. [N]			
Navigation vertical clearanc	0 = N/A		Navigation horizontal clearance	0 = N/A						
Minimum navigation vertical clearance, vertical lift bridge						Minimum vertical clearance over bridge roadway	99.99 m = 328.1 ft			
Minimum lateral underclearance reference feature	Highway beneath structure [H]									
Minimum lateral underclearance on right	27 m = 88.6 ft					Minimum lateral underclearance on left	1.9 m = 6.2 ft			
Minimum Vertical Underclearance	4.44 m = 14.6 ft		Minimum vertical underclearance reference feature	Highway beneath structure [H]						
Appraisal ratings - underclearances	Basically intolerable requiring high priority of corrective action [3]									

Repair and Replacement Plans

Type of work to be performed

Work done by

Bridge improvement cost

Roadway improvement cost

Length of structure improvement

Total project cost

Year of improvement cost estimate

Border bridge - state

Border bridge - percent responsibility of other state

Border bridge - structure number

Inspection and Sufficiency

Structure status	Open, no restriction [A]	Appraisal ratings - structural	Equal to present minimum criteria [6]
Condition ratings - superstructure	Good [7]	Appraisal ratings - roadway alignment	Better than present minimum criteria [7]
Condition ratings - substructure	Satisfactory [6]	Appraisal ratings - deck geometry	Superior to present desirable criteria [9]
Condition ratings - deck	Fair [5]		
Scour	Bridge not over waterway. [N]		
Channel and channel protection	Not applicable. [N]		
Appraisal ratings - water adequacy	N/A [N]	Status evaluation	
Pier or abutment protection		Sufficiency rating	
Culverts	Not applicable. Used if structure is not a culvert. [N]		
Traffic safety features - railings	Inspected feature meets currently acceptable standards. [1]		
Traffic safety features - transitions	Inspected feature meets currently acceptable standards. [1]		
Traffic safety features - approach guardrail	Inspected feature meets currently acceptable standards. [1]		
Traffic safety features - approach guardrail ends	Inspected feature meets currently acceptable standards. [1]		
Inspection date	September 1999 [999]	Designated inspection frequency	24 Months
Underwater inspection	Not needed [N]	Underwater inspection date	
Fracture critical inspection	Not needed [N]	Fracture critical inspection date	
Other special inspection	Not needed [N]	Other special inspection date	

HistoricBridges.org - National Bridge Inventory Data Sheet

2021 Inventory

The National Bridge Inventory contains data submitted by state transportation departments to the Federal Highway Administration in coded format.

Form Interface Design: www.historicbridges.org. Data Conversion Assistance By www.bridgehunter.com. None of the involved parties make any guarantee of accuracy.

Basic Information

Michigan [26]	Wayne County [163]	Dearborn [21000]	IN DEARBORN	42-19-27.97 = 42.324436	083-09-44.24 = -83.162289
11138	Highway agency district: 7	Owner State Highway Agency [01]	Maintenance responsibility	State Highway Agency [01]	
Route 12		RAMP FROM US-12EB	Toll On free road [3]	Features intersected I-94	
Design - main	Steel [3]	Design - approach		Kilometerpoint 28.5 km = 17.7 mi	
5	Stringer/Multi-beam or girder [02]	0	Other [00]	Year built 1948	Year reconstructed N/A [0000]
				Skew angle 99	Structure Flared
				Historical significance	Bridge is not eligible for the NRHP. [5]
Total length	79.8 m = 261.8 ft	Length of maximum span	19.5 m = 64.0 ft	Deck width, out-to-out	13.9 m = 45.6 ft
				Bridge roadway width, curb-to-curb	13.4 m = 44.0 ft
Inventory Route, Total Horizontal Clearance	13.4 m = 44.0 ft	Curb or sidewalk width - left	0 m = 0.0 ft	Curb or sidewalk width - right	0 m = 0.0 ft
Deck structure type	Concrete Cast-in-Place [1]				
Type of wearing surface	Latex Concrete or similar additive [3]				
Deck protection					
Type of membrane/wearing surface					

Weight Limits

Bypass, detour length	Method to determine inventory rating	Load Factor (LF) rating reported by rati	Inventory rating	62.2 metric ton = 68.4 tons
0 km = 0.0 mi	Method to determine operating rating	Load Factor (LF) rating reported by rati	Operating rating	97.2 metric ton = 106.9 tons
	Bridge posting	Equal to or above legal loads [5]	Design Load	MS 18 / HS 20 [5]

Functional Details

Average Daily Traffic	14880	Average daily truck traffi	0	%	Year	1982	Future average daily traffic	14880	Year	1977
Road classification	Other Principal Arterial (Urban) [14]		Lanes on structure	3		Approach roadway width	12.8 m = 42.0 ft			
Type of service on bridge	Highway [1]		Direction of traffic	1 - way traffic [1]		Bridge median				
Parallel structure designation	No parallel structure exists. [N]									
Type of service under bridge	Highway, with or without ped		Lanes under structure	6		Navigation control	Not applicable, no waterway. [N]			
Navigation vertical clearanc	0 = N/A		Navigation horizontal clearance	0 = N/A						
Minimum navigation vertical clearance, vertical lift bridge						Minimum vertical clearance over bridge roadway	99.99 m = 328.1 ft			
Minimum lateral underclearance reference feature	Highway beneath structure [H]									
Minimum lateral underclearance on right	30 m = 98.4 ft					Minimum lateral underclearance on left	1.8 m = 5.9 ft			
Minimum Vertical Underclearance	4.5 m = 14.8 ft		Minimum vertical underclearance reference feature	Highway beneath structure [H]						
Appraisal ratings - underclearances	Basically intolerable requiring high priority of corrective action [3]									

Repair and Replacement Plans

Type of work to be performed

Work done by

Bridge improvement cost

Roadway improvement cost

Length of structure improvement

Total project cost

Year of improvement cost estimate

Border bridge - state

Border bridge - percent responsibility of other state

Border bridge - structure number

Inspection and Sufficiency

Structure status	Open, no restriction [A]	Appraisal ratings - structural	Better than present minimum criteria [7]
Condition ratings - superstructure	Good [7]	Appraisal ratings - roadway alignment	Equal to present desirable criteria [8]
Condition ratings - substructure	Good [7]	Appraisal ratings - deck geometry	Somewhat better than minimum adequacy to tolerate being left in place as is [5]
Condition ratings - deck	Very Good [8]		
Scour	Bridge not over waterway. [N]		
Channel and channel protection	Not applicable. [N]		
Appraisal ratings - water adequacy	N/A [N]	Status evaluation	
Pier or abutment protection		Sufficiency rating	
Culverts	Not applicable. Used if structure is not a culvert. [N]		
Traffic safety features - railings	Inspected feature meets currently acceptable standards. [1]		
Traffic safety features - transitions	Inspected feature meets currently acceptable standards. [1]		
Traffic safety features - approach guardrail	Inspected feature meets currently acceptable standards. [1]		
Traffic safety features - approach guardrail ends	Inspected feature meets currently acceptable standards. [1]		
Inspection date	September 1999 [999]	Designated inspection frequency	24 Months
Underwater inspection	Not needed [N]	Underwater inspection date	
Fracture critical inspection	Not needed [N]	Fracture critical inspection date	
Other special inspection	Not needed [N]	Other special inspection date	