

HistoricBridges.org - National Bridge Inventory Data Sheet

2010 Inventory

The National Bridge Inventory contains data submitted by state transportation departments to the Federal Highway Administration in coded format.

Form Interface Design: www.historicbridges.org. Data Conversion Assistance By www.bridgehunter.com. None of the involved parties make any guarantee of accuracy.

Basic Information

Michigan [26]	Genesee County [049]	Fenton [27780]	NORTHOFUS-23RAMP	42-48-54 = 42.815000	083-43-38 = - 83.727222
25306H00033B010	Highway agency district 4	Owner County Highway Agency [02]	Maintenance responsibility	County Highway Agency [02]	
Route 0		NORTH ROAD	Toll On free road [3]	Features intersected SHIAWASSEE RIVER	
Design - main	Steel [3]	Design - approach		Kilometerpoint	309.8 km = 192.1 mi
1	Stringer/Multi-beam or girder [02]	0	Other [00]	Year built	1928
				Year reconstructed	N/A [0000]
				Skew angle	0
				Structure Flared	
				Historical significance	Bridge is not eligible for the NRHP. [5]
Total length	10.6 m = 34.8 ft	Length of maximum span	10.3 m = 33.8 ft	Deck width, out-to-out	10.8 m = 35.4 ft
				Bridge roadway width, curb-to-curb	9.1 m = 29.9 ft
Inventory Route, Total Horizontal Clearance	9.1 m = 29.9 ft	Curb or sidewalk width - left	0 m = 0.0 ft	Curb or sidewalk width - right	0 m = 0.0 ft
Deck structure type	Concrete Cast-in-Place [1]				
Type of wearing surface	Bituminous [6]				
Deck protection					
Type of membrane/wearing surface					

Weight Limits

Bypass, detour length	Method to determine inventory rating	Load Factor(LF) [1]	Inventory rating	42.1 metric ton = 46.3 tons
0 km = 0.0 mi	Method to determine operating rating	Load Factor(LF) [1]	Operating rating	82.5 metric ton = 90.8 tons
	Bridge posting	Equal to or above legal loads [5]	Design Load	MS 18+Mod / HS 20+Mod [6]

Functional Details

Average Daily Traffic	6210	Average daily truck traffi	2	%	Year	1997	Future average daily traffic	11180	Year	2017
Road classification	Minor Collector (Rural) [08]		Lanes on structure	2		Approach roadway width	11 m = 36.1 ft			
Type of service on bridge	Highway [1]		Direction of traffic	2 - way traffic [2]		Bridge median				
Parallel structure designation	No parallel structure exists. [N]									
Type of service under bridge	Waterway [5]		Lanes under structure	0		Navigation control				
Navigation vertical clearanc	0 = N/A		Navigation horizontal clearance	0 = N/A						
Minimum navigation vertical clearance, vertical lift bridge						Minimum vertical clearance over bridge roadway	99.99 m = 328.1 ft			
Minimum lateral underclearance reference feature	Feature not a highway or railroad [N]									
Minimum lateral underclearance on right	99.9 = Unlimited					Minimum lateral underclearance on left	0 = N/A			
Minimum Vertical Underclearance	0 = N/A		Minimum vertical underclearance reference feature	Feature not a highway or railroad [N]						
Appraisal ratings - underclearances	N/A [N]									

Repair and Replacement Plans

Type of work to be performed

Work done by

Bridge improvement cost

Roadway improvement cost

Length of structure improvement

Total project cost

Year of improvement cost estimate

Border bridge - state

Border bridge - percent responsibility of other state

Border bridge - structure number

Inspection and Sufficiency

Structure status	Open, no restriction [A]	Appraisal ratings - structural	Equal to present minimum criteria [6]
Condition ratings - superstructure	Satisfactory [6]	Appraisal ratings - roadway alignment	Equal to present desirable criteria [8]
Condition ratings - substructure	Satisfactory [6]	Appraisal ratings - deck geometry	Basically intolerable requiring high priority of corrective action [3]
Condition ratings - deck	Satisfactory [6]		
Scour	Bridge is scour critical; bridge foundations determined to be unstable. [3]		
Channel and channel protection	Bank is beginning to slump. River control devices and embankment protection have widespread minor damage. There is minor stream bed movement evident. Debris is restricting the channel slightly. [6]		
Appraisal ratings - water adequacy	Equal to present desirable criteria [8]	Status evaluation	Functionally obsolete [2]
Pier or abutment protection		Sufficiency rating	78
Culverts	Not applicable. Used if structure is not a culvert. [N]		
Traffic safety features - railings			
Traffic safety features - transitions			
Traffic safety features - approach guardrail			
Traffic safety features - approach guardrail ends			
Inspection date	December 2008 [1208]	Designated inspection frequency	24 Months
Underwater inspection	Not needed [N]	Underwater inspection date	
Fracture critical inspection	Not needed [N]	Fracture critical inspection date	
Other special inspection	Not needed [N]	Other special inspection date	