

The National Bridge Inventory contains data submitted by state transportation departments to the Federal Highway Administration in coded format.
 Form Interface Design: www.historicbridges.org. Data Conversion Assistance By www.bridgehunter.com. None of the involved parties make any guarantee of accuracy.

Basic Information

Michigan [26]	Gogebic County [053]	Watersmeet [84380]	SEC 15 WATERSMEET TWP	46-17-50 = 46.297222	089-25-00 = - 89.416667
3028	Highway agency district 1	Owner County Highway Agency [02]	Maintenance responsibility	County Highway Agency [02]	
Route 0	OLD US-2	Toll On free road [3]	Features intersected	CISCO BR ONTONAGON RIVER	
Design - main Steel [3]	Design - approach	Kilometerpoint 115.1 km = 71.4 mi	Year built 1927	Year reconstructed	
1	Stringer/Multi-beam or girder [02]	0	Other [00]	Skew angle 30	Structure Flared
		Historical significance		Bridge is not eligible for the NRHP. [5]	
Total length 18.2 m = 59.7 ft	Length of maximum span 17.6 m = 57.7 ft	Deck width, out-to-out 11.1 m = 36.4 ft	Bridge roadway width, curb-to-curb 9.1 m = 29.9 ft		
Inventory Route, Total Horizontal Clearance 9.1 m = 29.9 ft	Curb or sidewalk width - left 0 m = 0.0 ft	Curb or sidewalk width - right 0 m = 0.0 ft			
Deck structure type	Concrete Cast-in-Place [1]				
Type of wearing surface	Bituminous [6]				
Deck protection					
Type of membrane/wearing surface					

Weight Limits

Bypass, detour length 0.3 km = 0.2 mi	Method to determine inventory rating	Load Factor(LF) [1]	Inventory rating	33 metric ton = 36.3 tons
	Method to determine operating rating	Load Factor(LF) [1]	Operating rating	55 metric ton = 60.5 tons
Bridge posting	Equal to or above legal loads [5]		Design Load	M 13.5 / H 15 [2]

Functional Details

Average Daily Traffic	48	Average daily truck traffi	0	%	Year	1998	Future average daily traffic	48	Year	2018
Road classification	Local (Rural) [09]		Lanes on structure	2		Approach roadway width	8.5 m = 27.9 ft			
Type of service on bridge	Highway [1]		Direction of traffic	2 - way traffic [2]		Bridge median				
Parallel structure designation	No parallel structure exists. [N]									
Type of service under bridge	Waterway [5]		Lanes under structure	0		Navigation control				
Navigation vertical clearanc	0 = N/A		Navigation horizontal clearance	0 = N/A						
Minimum navigation vertical clearance, vertical lift bridge			Minimum vertical clearance over bridge roadway	99.99 m = 328.1 ft						
Minimum lateral underclearance reference feature	Feature not a highway or railroad [N]									
Minimum lateral underclearance on right	99.9 = Unlimited				Minimum lateral underclearance on left	0 = N/A				
Minimum Vertical Underclearance	0 = N/A		Minimum vertical underclearance reference feature	Feature not a highway or railroad [N]						
Appraisal ratings - underclearances	N/A [N]									

Repair and Replacement Plans

Type of work to be performed	Work done by		Work to be done by contract [1]							
Replacement of bridge or other structure because of substandard load carrying capacity or substantial bridge roadway geometry. [31]	Bridge improvement cost	306000	Roadway improvement cost	31000						
	Length of structure improvement	21.8 m = 71.5 ft		Total project cost	421000					
	Year of improvement cost estimate									
	Border bridge - state				Border bridge - percent responsibility of other state					
	Border bridge - structure number									

Inspection and Sufficiency

Structure status	<input type="text" value="Open, no restriction [A]"/>	Appraisal ratings - structural	<input type="text" value="Meets minimum tolerable limits to be left in place as is [4]"/>
Condition ratings - superstructure	<input type="text" value="Poor [4]"/>	Appraisal ratings - roadway alignment	<input type="text" value="Equal to present desirable criteria [8]"/>
Condition ratings - substructure	<input type="text" value="Fair [5]"/>	Appraisal ratings - deck geometry	<input type="text" value="Better than present minimum criteria [7]"/>
Condition ratings - deck	<input type="text" value="Fair [5]"/>		
Scour	<input type="text" value="Bridge is scour critical; bridge foundations determined to be unstable. [3]"/>		
Channel and channel protection	<input type="text" value="Bank protection is in need of minor repairs. River control devices and embankment protection have a little minor damage. Banks and/or channel have minor amounts of drift. [7]"/>		
Appraisal ratings - water adequacy	<input type="text" value="Better than present minimum criteria [7]"/>	Status evaluation	<input type="text" value="Structurally deficient [1]"/>
Pier or abutment protection	<input type="text"/>	Sufficiency rating	<input type="text" value="69"/>
Culverts	<input type="text" value="Not applicable. Used if structure is not a culvert. [N]"/>		
Traffic safety features - railings	<input type="text"/>		
Traffic safety features - transitions	<input type="text"/>		
Traffic safety features - approach guardrail	<input type="text"/>		
Traffic safety features - approach guardrail ends	<input type="text"/>		
Inspection date	<input type="text" value="September 2010 [0910]"/>	Designated inspection frequency	<input type="text" value="24"/> Months
Underwater inspection	<input type="text" value="Not needed [N]"/>	Underwater inspection date	<input type="text"/>
Fracture critical inspection	<input type="text" value="Not needed [N]"/>	Fracture critical inspection date	<input type="text"/>
Other special inspection	<input type="text" value="Not needed [N]"/>	Other special inspection date	<input type="text"/>