

The National Bridge Inventory contains data submitted by state transportation departments to the Federal Highway Administration in coded format.  
 Form Interface Design: www.historicbridges.org. Data Conversion Assistance By www.bridgehunter.com. None of the involved parties make any guarantee of accuracy.

**Basic Information**

Michigan [26]	St. Clair County [147]	Riley [68620]	SEC. 17-18 RILEY TWP.	42-56-44 = 42.945556	082-50-31 = - 82.841944
77200047000B010	Highway agency district 7	Owner County Highway Agency [02]	Maintenance responsibility	County Highway Agency [02]	
Route 0	RILEY CENTER ROAD	Toll On free road [3]	Features intersected	BELLE RIVER	
Design - main Steel [3]	Design - approach	Kilometerpoint 558.3 km = 346.1 mi	Year built 1935	Year reconstructed N/A [0000]	
1 Stringer/Multi-beam or girder [02]	0 Other [00]	Skew angle 0	Structure Flared		
		Historical significance	Bridge is not eligible for the NRHP. [5]		
Total length 18.9 m = 62.0 ft	Length of maximum span 18.4 m = 60.4 ft	Deck width, out-to-out 7.3 m = 24.0 ft	Bridge roadway width, curb-to-curb	6.1 m = 20.0 ft	
Inventory Route, Total Horizontal Clearance 6.1 m = 20.0 ft	Curb or sidewalk width - left 0 m = 0.0 ft	Curb or sidewalk width - right	0 m = 0.0 ft		
Deck structure type	Concrete Cast-in-Place [1]				
Type of wearing surface	Bituminous [6]				
Deck protection					
Type of membrane/wearing surface					

**Weight Limits**

Bypass, detour length 0.3 km = 0.2 mi	Method to determine inventory rating	Load Factor(LF) [1]	Inventory rating	31 metric ton = 34.1 tons
	Method to determine operating rating	Load Factor(LF) [1]	Operating rating	51.8 metric ton = 57.0 tons
Bridge posting	30.0 - 39.9 % below [1]		Design Load	MS 18+Mod / HS 20+Mod [6]

### Functional Details

Average Daily Traffic	2015	Average daily truck traffi	6	%	Year	2007	Future average daily traffic	4415	Year	2027
Road classification	Major Collector (Rural) [07]		Lanes on structure	2		Approach roadway width	9.8 m = 32.2 ft			
Type of service on bridge	Highway [1]		Direction of traffic	2 - way traffic [2]		Bridge median				
Parallel structure designation	No parallel structure exists. [N]									
Type of service under bridge	Waterway [5]		Lanes under structure	0		Navigation control				
Navigation vertical clearanc	0 = N/A		Navigation horizontal clearance	0 = N/A						
Minimum navigation vertical clearance, vertical lift bridge			Minimum vertical clearance over bridge roadway	99.99 m = 328.1 ft						
Minimum lateral underclearance reference feature	Feature not a highway or railroad [N]									
Minimum lateral underclearance on right	99.9 = Unlimited					Minimum lateral underclearance on left	0 = N/A			
Minimum Vertical Underclearance	0 = N/A		Minimum vertical underclearance reference feature	Feature not a highway or railroad [N]						
Appraisal ratings - underclearances	N/A [N]									

### Repair and Replacement Plans

Type of work to be performed	Work done by	Work to be done by contract [1]								
Replacement of bridge or other structure because of substandard load carrying capacity or substantial bridge roadway geometry. [31]	Bridge improvement cost	907000	Roadway improvement cost	173000						
	Length of structure improvement	30.5 m = 100.1 ft		Total project cost	1080000					
	Year of improvement cost estimate	2006								
	Border bridge - state				Border bridge - percent responsibility of other state					
	Border bridge - structure number									

## Inspection and Sufficiency

Structure status	Posted for load [P]	Appraisal ratings - structural	Meets minimum tolerable limits to be left in place as is [4]
Condition ratings - superstructure	Poor [4]	Appraisal ratings - roadway alignment	Somewhat better than minimum adequacy to tolerate being left in place as is [5]
Condition ratings - substructure	Satisfactory [6]	Appraisal ratings - deck geometry	Basically intolerable requiring high priority of replacement [2]
Condition ratings - deck	Serious [3]		
Scour	Bridge foundations determined to be stable for assessed or calculated scour condition. [5]		
Channel and channel protection	Bank protection is being eroded. River control devices and/or embankment have major damage. Trees and rush restrict the channel. [5]		
Appraisal ratings - water adequacy	Somewhat better than minimum adequacy to tolerate being left in place as is [5]	Status evaluation	Structurally deficient [1]
Pier or abutment protection		Sufficiency rating	45.7
Culverts	Not applicable. Used if structure is not a culvert. [N]		
Traffic safety features - railings			
Traffic safety features - transitions			
Traffic safety features - approach guardrail			
Traffic safety features - approach guardrail ends			
Inspection date	January 2010 [0110]	Designated inspection frequency	12 Months
Underwater inspection	Not needed [N]	Underwater inspection date	
Fracture critical inspection	Not needed [N]	Fracture critical inspection date	
Other special inspection	Not needed [N]	Other special inspection date	