The National Bridge Inventory contains data submitted by state transportion departments to the Federal Highway Administration in coded format.

Form Interface Design: www.historicbridges.org. Data Conversion Assistance By www.bridgehunter.com. None of the involved parties make any guarantee of accuracy.

Basic Info	ormation									43-42-36 =	084-58-06 = -
Michigan [26] Isabella County [073]]	Nottawa [59360]		0.2 M S NW COR SEC 7 T15N			43.710000	84.968333		
37200036000B460 Highway ag		Highway agend	cy district 4	Owner County Highwa		y Agency [02] Main		Maintenance	e responsibility	County Highway	Agency [02]
Route 3725 WOODRUFF ROAD					Toll On free road [3] Features intersected COLDWATI			ER RIVER			
main	Concrete [1] Girder and f	loorbeam system [03	Design - approach Oth	ner [00]		Kilometerp Year built Skew angle Historical s	1926 e 45	Structure F	constructed N/A	[0000]	
Historical significance Bridge is not eligible for the NRHP. [5] Total length 24.3 m = 79.7 ft Length of maximum span 12.2 m = 40.0 ft Deck width, out-to-out 7.6 m = 24.9 ft Bridge roadway width, curb-to-curb 6.4 m = 21.0 ft Inventory Route, Total Horizontal Clearance 6.5 m = 21.3 ft Curb or sidewalk width - left O m = 0.0 ft Curb or sidewalk width - right											
Deck structure type Concrete Cast-in-Place				Place [1]							
Type of wearing surface Bituminous [6]											
Deck prote	ection										
Type of m	embrane/wea	aring surface									
Weight Li	mits										
Bypass, detour length Method to determine inventory rating			ng Allo	Allowable Stress(AS) [2]		Inv	entory rating	25.1 metric ton	= 27.6 tons		
0.5 km = 0.3 mi Method to determine operating rating			ng Allo	Allowable Stress(AS) [2]		Op	erating rating	32.7 metric ton = 36.0 tons			
Bridge posting						De	Design Load M 13.5 / H 15 [2]				

Functional Details							
Average Daily Traffic 1154 Average daily tr	ıck traffi 0 % Year 2007 Future average daily traffic	2084 Year 2027					
Road classification Major Collector (Rural) [07]	Lanes on structure 2	Approach roadway width 9.1 m = 29.9 ft					
Type of service on bridge Highway [1]	Direction of traffic 2 - way traffic [2]	Bridge median					
Parallel structure designation No parallel structure	e exists. [N]						
Type of service under bridge Waterway [5]	Lanes under structure 0 Navigation control						
Navigation vertical clearanc 0 = N/A	Navigation horizontal clearance 0 = N/A						
Minimum navigation vertical clearance, vertical lift bridge Minimum vertical clearance over bridge roadway 99.99 m = 328.1 ft							
Minimum lateral underclearance reference feature Feature not a highway or railroad [N]							
Minimum lateral underclearance on right 99.9 = Unlimited Minimum lateral underclearance on left 0 = N/A							
Minimum Vertical Underclearance 0 = N/A Minimum vertical underclearance reference feature Feature not a highway or railroad [N]							
Appraisal ratings - underclearances N/A [N]							
Repair and Replacement Plans							
Type of work to be performed	Work done by Work to be done by contract [1]						
Replacement of bridge or other structure because of substandard load carrying capacity or substantial	Bridge improvement cost 400000 Roadway imp	provement cost 35000					
bridge roadway geometry. [31]	Length of structure improvement 32.9 m = 107.9 ft	Total project cost 435000					
	Year of improvement cost estimate 2004						
	Border bridge - state Bo	order bridge - percent responsibility of other state					
	Border bridge - structure number						

Inspection and Sufficiency								
Structure status Posted for lo	ad [P]	Appraisal ratings - structural	Basically intolerable requiring high priority of corrrective action [3]					
Condition ratings - superstructur	Serious [3]	Appraisal ratings - roadway alignment	Equal to present mini	resent minimum criteria [6]				
Condition ratings - substructure	Poor [4]	Appraisal ratings -	Basically intolerable r	acement [2]				
Condition ratings - deck	Serious [3]	deck geometry						
Scour	Bridge is scour critical; bridge	Bridge is scour critical; bridge foundations determined to be unstable. [3]						
Channel and channel protection	Bank and embankment protected debris are in the channel. [4]	Bank and embankment protection is severely undermined. River control devices have severe damage. Large deposits of debris are in the channel. [4]						
Appraisal ratings - water adequac	Better than present minimum	criteria [7]	Status eva	luation Structurally defic	ient [1]			
Pier or abutment protection			Sufficienc	rating 23.4				
Culverts Not applicable. Used	if structure is not a culvert. [N]							
Traffic safety features - railings Inpected feature meets currently acceptable standards. [1]								
Traffic safety features - transition	ns							
Traffic safety features - approach	h guardrail							
Traffic safety features - approach guardrail ends								
Inspection date May 2009 [0509] Designated inspection frequency 24 Months								
Underwater inspection	Not needed [N]	Underwater inspec						
Fracture critical inspection	Not needed [N]	Fracture critical ins	spection date					
Other special inspection Not needed [N] Other special inspection date								