

HistoricBridges.org - National Bridge Inventory Data Sheet

2011 Inventory

The National Bridge Inventory contains data submitted by state transportation departments to the Federal Highway Administration in coded format.

Form Interface Design: www.historicbridges.org. Data Conversion Assistance By www.bridgehunter.com. None of the involved parties make any guarantee of accuracy.

Basic Information

New Hampshire [33]	Merrimack County [013]	Henniker [35540]	.09 MI FR NH RTE 114	43-10-26 = 43.173889	071-49-01 = - 71.816944
012001230010600	Highway agency district 5	Owner City or Municipal Highway Agency [04]	Maintenance responsibility	City or Municipal Highway Agency [04]	
Route 0		RAMSDELL ROAD	Toll On free road [3]	Features intersected CONTOOCOOK RIVER	
Design - main	Steel [3]	Design - approach		Kilometerpoint 14.5 km = 9.0 mi	
1	Truss - Thru [10]	0	Other [00]	Year built 1937	Year reconstructed 2008
				Skew angle 0	Structure Flared
				Historical significance Bridge is possibly eligible for the NRHP. [3]	
Total length 33.8 m = 110.9 ft	Length of maximum span 32.9 m = 107.9 ft	Deck width, out-to-out 6.1 m = 20.0 ft	Bridge roadway width, curb-to-curb 5.5 m = 18.0 ft		
Inventory Route, Total Horizontal Clearance 5.5 m = 18.0 ft	Curb or sidewalk width - left 1.2 m = 3.9 ft	Curb or sidewalk width - right 0.2 m = 0.7 ft			
Deck structure type	Closed Grating [4]				
Type of wearing surface					
Deck protection					
Type of membrane/wearing surface					

Weight Limits

Bypass, detour length 0.2 km = 0.1 mi	Method to determine inventory rating	Load Factor(LF) [1]	Inventory rating 34.6 metric ton = 38.1 tons
	Method to determine operating rating	Load Factor(LF) [1]	Operating rating 54.2 metric ton = 59.6 tons
Bridge posting	Equal to or above legal loads [5]	Design Load	M 13.5 / H 15 [2]

Functional Details

Average Daily Traffic	480	Average daily truck traffi	4	%	Year	2006	Future average daily traffic	710	Year	2032
Road classification	Local (Rural) [09]		Lanes on structure	2		Approach roadway width	6.1 m = 20.0 ft			
Type of service on bridge	Highway-pedestrian [5]		Direction of traffic	2 - way traffic [2]		Bridge median				
Parallel structure designation	No parallel structure exists. [N]									
Type of service under bridge	Waterway [5]		Lanes under structure	0		Navigation control				
Navigation vertical clearanc	0 = N/A		Navigation horizontal clearance	0 = N/A						
Minimum navigation vertical clearance, vertical lift bridge	0 m = 0.0 ft					Minimum vertical clearance over bridge roadway	4.18 m = 13.7 ft			
Minimum lateral underclearance reference feature	Feature not a highway or railroad [N]									
Minimum lateral underclearance on right	99.9 = Unlimited					Minimum lateral underclearance on left	0 = N/A			
Minimum Vertical Underclearance	0 = N/A		Minimum vertical underclearance reference feature	Feature not a highway or railroad [N]						
Appraisal ratings - underclearances	N/A [N]									

Repair and Replacement Plans

Type of work to be performed	Work done by	Work to be done by contract [1]		
Replacement of bridge or other structure because of substandard load carrying capacity or substantial bridge roadway geometry. [31]	Bridge improvement cost	2000000	Roadway improvement cost	200000
	Length of structure improvement	33.8 m = 110.9 ft	Total project cost	2500000
	Year of improvement cost estimate	2011		
	Border bridge - state		Border bridge - percent responsibility of other state	
	Border bridge - structure number			

Inspection and Sufficiency

Structure status	Open, no restriction [A]	Appraisal ratings - structural	Better than present minimum criteria [7]
Condition ratings - superstructure	Very Good [8]	Appraisal ratings - roadway alignment	Meets minimum tolerable limits to be left in place as is [4]
Condition ratings - substructure	Good [7]	Appraisal ratings - deck geometry	Basically intolerable requiring high priority of replacement [2]
Condition ratings - deck	Excellent [9]		
Scour	Bridge foundations determined to be stable for the assessed or calculated scour condition. [8]		
Channel and channel protection	Banks are protected or well vegetated. River control devices such as spur dikes and embankment protection are not required or are in a stable condition. [8]		
Appraisal ratings - water adequacy	Somewhat better than minimum adequacy to tolerate being left in place as is [5]	Status evaluation	
Pier or abutment protection		Sufficiency rating	70.9
Culverts	Not applicable. Used if structure is not a culvert. [N]		
Traffic safety features - railings			
Traffic safety features - transitions	Inspected feature meets currently acceptable standards. [1]		
Traffic safety features - approach guardrail	Inspected feature meets currently acceptable standards. [1]		
Traffic safety features - approach guardrail ends	Inspected feature meets currently acceptable standards. [1]		
Inspection date	February 2010 [0210]	Designated inspection frequency	24 Months
Underwater inspection	Not needed [N]	Underwater inspection date	
Fracture critical inspection	Every two years [Y24]	Fracture critical inspection date	October 2008 [1008]
Other special inspection	Every two years [Y24]	Other special inspection date	February 2010 [0210]