

# HistoricBridges.org - National Bridge Inventory Data Sheet

2009 Inventory

The National Bridge Inventory contains data submitted by state transportation departments to the Federal Highway Administration in coded format.

Form Interface Design: www.historicbridges.org. Data Conversion Assistance By www.bridgehunter.com. None of the involved parties make any guarantee of accuracy.

## Basic Information

New York [36]	Clinton County [019]	Peru [57375]	4.6 MI N JCT US 9 & SH 22	44-33-31 = 44.558611	073-26-55 = - 73.448611
1005950	Highway agency district	71	Owner	State Highway Agency [01]	Maintenance responsibility
Route	9		RTE 9	Toll	On free road [3]
Design - main	Steel [3]	Design - approach		Kilometerpoint	441.8 km = 273.9 mi
1	Truss - Thru [10]	0	Other [00]	Year built	1940
				Year reconstructed	N/A [0000]
				Skew angle	0
				Structure Flared	
				Historical significance	Bridge is on the NRHP. [1]
Total length	77.7 m = 254.9 ft	Length of maximum span	77.7 m = 254.9 ft	Deck width, out-to-out	15.2 m = 49.9 ft
Inventory Route, Total Horizontal Clearance	12.8 m = 42.0 ft	Curb or sidewalk width - left	0.8 m = 2.6 ft	Curb or sidewalk width - right	0.8 m = 2.6 ft
Deck structure type	Concrete Cast-in-Place [1]				
Type of wearing surface	Integral Concrete (separate non-modified layer of concrete added to structural deck) [2]				
Deck protection	Epoxy Coated Reinforcing [1]				
Type of membrane/wearing surface					

## Weight Limits

Bypass, detour length	Method to determine inventory rating	Load Factor(LF) [1]	Inventory rating	37.2 metric ton = 40.9 tons
1.1 km = 0.7 mi	Method to determine operating rating	Load Factor(LF) [1]	Operating rating	59.9 metric ton = 65.9 tons
	Bridge posting	Equal to or above legal loads [5]	Design Load	M 18 / H 20 [4]

### Functional Details

Average Daily Traffic	2459	Average daily truck traffi	10	%	Year	2007	Future average daily traffic	3075	Year	2027
Road classification	Minor Arterial (Rural) [06]		Lanes on structure	2		Approach roadway width	10 m = 32.8 ft			
Type of service on bridge	Highway [1]		Direction of traffic	2 - way traffic [2]		Bridge median				
Parallel structure designation	No parallel structure exists. [N]									
Type of service under bridge	Waterway [5]		Lanes under structure	0		Navigation control				
Navigation vertical clearanc	0 = N/A		Navigation horizontal clearance	0 = N/A						
Minimum navigation vertical clearance, vertical lift bridge						Minimum vertical clearance over bridge roadway	4.62 m = 15.2 ft			
Minimum lateral underclearance reference feature	Feature not a highway or railroad [N]									
Minimum lateral underclearance on right	99.9 = Unlimited					Minimum lateral underclearance on left	0 = N/A			
Minimum Vertical Underclearance	0 = N/A		Minimum vertical underclearance reference feature	Feature not a highway or railroad [N]						
Appraisal ratings - underclearances	N/A [N]									

### Repair and Replacement Plans

Type of work to be performed	Work done by	Work to be done by contract [1]		
Widening of existing bridge with deck rehabilitation or replacement. [34]	Bridge improvement cost	531000	Roadway improvement cost	316000
	Length of structure improvement	77.7 m = 254.9 ft	Total project cost	847000
	Year of improvement cost estimate	2009		
	Border bridge - state		Border bridge - percent responsibility of other state	
	Border bridge - structure number			

## Inspection and Sufficiency

Structure status	Open, no restriction [A]	Appraisal ratings - structural	Equal to present minimum criteria [6]
Condition ratings - superstructure	Satisfactory [6]	Appraisal ratings - roadway alignment	Equal to present desirable criteria [8]
Condition ratings - substructure	Good [7]	Appraisal ratings - deck geometry	Equal to present minimum criteria [6]
Condition ratings - deck	Satisfactory [6]		
Scour	Bridge foundations determined to be stable for assessed or calculated scour conditions; field review indicates action is required. [4]		
Channel and channel protection	Banks are protected or well vegetated. River control devices such as spur dikes and embankment protection are not required or are in a stable condition. [8]		
Appraisal ratings - water adequacy	Somewhat better than minimum adequacy to tolerate being left in place as is [5]	Status evaluation	
Pier or abutment protection		Sufficiency rating	92.7
Culverts	Not applicable. Used if structure is not a culvert. [N]		
Traffic safety features - railings	Inspected feature meets currently acceptable standards. [1]		
Traffic safety features - transitions			
Traffic safety features - approach guardrail	Inspected feature meets currently acceptable standards. [1]		
Traffic safety features - approach guardrail ends	Inspected feature meets currently acceptable standards. [1]		
Inspection date	August 2009 [0809]	Designated inspection frequency	24 Months
Underwater inspection	Not needed [N]	Underwater inspection date	
Fracture critical inspection	Every two years [Y24]	Fracture critical inspection date	August 2009 [0809]
Other special inspection	Not needed [N]	Other special inspection date	