



This is a digital copy of a book that was preserved for generations on library shelves before it was carefully scanned by Google as part of a project to make the world's books discoverable online.

It has survived long enough for the copyright to expire and the book to enter the public domain. A public domain book is one that was never subject to copyright or whose legal copyright term has expired. Whether a book is in the public domain may vary country to country. Public domain books are our gateways to the past, representing a wealth of history, culture and knowledge that's often difficult to discover.

Marks, notations and other marginalia present in the original volume will appear in this file - a reminder of this book's long journey from the publisher to a library and finally to you.

Usage guidelines

Google is proud to partner with libraries to digitize public domain materials and make them widely accessible. Public domain books belong to the public and we are merely their custodians. Nevertheless, this work is expensive, so in order to keep providing this resource, we have taken steps to prevent abuse by commercial parties, including placing technical restrictions on automated querying.

We also ask that you:

- + *Make non-commercial use of the files* We designed Google Book Search for use by individuals, and we request that you use these files for personal, non-commercial purposes.
- + *Refrain from automated querying* Do not send automated queries of any sort to Google's system: If you are conducting research on machine translation, optical character recognition or other areas where access to a large amount of text is helpful, please contact us. We encourage the use of public domain materials for these purposes and may be able to help.
- + *Maintain attribution* The Google "watermark" you see on each file is essential for informing people about this project and helping them find additional materials through Google Book Search. Please do not remove it.
- + *Keep it legal* Whatever your use, remember that you are responsible for ensuring that what you are doing is legal. Do not assume that just because we believe a book is in the public domain for users in the United States, that the work is also in the public domain for users in other countries. Whether a book is still in copyright varies from country to country, and we can't offer guidance on whether any specific use of any specific book is allowed. Please do not assume that a book's appearance in Google Book Search means it can be used in any manner anywhere in the world. Copyright infringement liability can be quite severe.

About Google Book Search

Google's mission is to organize the world's information and to make it universally accessible and useful. Google Book Search helps readers discover the world's books while helping authors and publishers reach new audiences. You can search through the full text of this book on the web at <http://books.google.com/>

THE
Engineering Record

BUILDING RECORD AND SANITARY ENGINEER

VOLUME 58

July—December, 1908

McGraw Publishing Co.
239 West 39th St.
New York

liminaries are now so far advanced that it is believed the work will be completed on or before schedule time.

The cable wires will be carried back and forth across the river, in bights, each loop being secured to the permanent shoe for subsequent connection to the anchorage eyebars, and the process being maintained continuously from both sides of the


to support the sheaves of the carrying and hauling cables used for the placing of the strand wires. The platforms are braced against excessive deflection and against wind pressure by back stays from each tower and by storm cables curved upward and connected to them at intervals of about 54 ft. by suspender ropes.

The details of construction are very simple.

stantial vertical posts on every floorbeam. The floor boards, $1\frac{1}{2}$ in. apart in the clear, are laid on three lines of stringers overlapping and bolted together at the ends where they are dapped 3 in. and carefully fitted to the floorbeams thus materially stiffening the cables. The floorbeams are tightly secured by U-bolt clamps to the temporary cables, each of which is made with four $1\frac{3}{4}$ -in. steel-wire ropes.

At the tops of the towers the falsework cables pass over cast-iron saddles riveted between the webs of pairs of 15-in. channels, 14 ft. long, which form temporary girders rigidly connected to the steel work of the towers. At the anchorage piers where these cables deflect from the curves of the catenaries to approximate tangents, leading to their fastenings, they are deflected horizontally and are supported in cast-iron saddles provided with curved grooved bearings, which are seated on the top flanges of built girders. The latter are composed of a pair of 15-in. channels $35\frac{1}{2}$ ft. long, with top and bottom flange cover plates, which are secured to the masonry and will be removed after the completion of the cables. The ends of the cables are socketed, in the usual standard way, to clevises with pin connections to the anchorages.

The transverse bridge connecting the four platforms at the center of the main span consists merely of a horizontal platform 6 ft. wide laid on the top chords of a pair of queen post trusses with pin-connected suspension at the ends to special floorbeams in the working platforms. The trusses, weighing only about 2600 lb. each, are 68 ft. long and 4 ft. 6 in. deep on centers, and are entirely of wood, except for the bottom chords, which are round steel rods with pin connections and sleeve-nut adjustments. The top chords and the verti-




Near View of the Temporary Footbridges on the Manhattan Bridge.

river, will provide for placing sixteen wires simultaneously. When the 80,000 ft. of wire is unwound from a reel its end is coupled to the end of the wire on the adjacent full reel in the reel frame on the anchorage and the operation of stringing and adjusting continues until the 256 wires of the strand are in place. The successive loops will be squeezed together to form the strands, seized with wire at frequent intervals and finally lowered a few feet vertically from their temporary positions, placed in the permanent saddles and on the anchor chain pins and adjusted to their correct deflection for position in the unloaded cable. When all the strands of cable are completed in place, they will be assembled into one solid mass to make the finished cable.

These operations will require workmen at all points of the length of the cable between anchorages, and although the cable will be at all times self-supporting, working platforms must be provided for the men. As the men work at the cables in situ, the working platforms must conform in elevation to the catenary curve of the cables, and, as great rigidity is not essential, a suspended platform is obviously most convenient, economical and suitable. A platform has, therefore, been built on light temporary cables parallel to and just below the main cables which will serve as a convenient support for the workmen, and after the completion of the cables will be removed before the erection of the trusses and floor platforms of the permanent span.

The falsework consists essentially of four platforms, 8 ft. wide, concentric with the main cables and about 30 in. in the clear below them. On each side of the bridge axis the two platforms, 28 ft. apart on centers, are carried by double cantilever floorbeams, $35\frac{1}{2}$ ft. long, which are clamped to the upper sides of the temporary cables, 21 ft. apart on centers. Access from one platform to another can be had only at the anchorages, at the tops of the towers, and by a single transverse bridge at the center of the channel span. Each platform carries nine approximately equidistant small towers



Temporary Construction Footbridges across the Main Span.

Special care was exercised in the design to combine the greatest practical lightness and strength. Everything except the wire ropes is made of light wooden planks of a maximum cross-section of 3×12 in. Details are very carefully designed and all connections are thoroughly bolted with washer bearings. Each working platform is protected by a pair of wire rope hand rails, secured to sub-

cal posts are X-braced with 2×8 -in. planks, spiked on, and the other connections are very simply detailed and thoroughly bolted, as indicated in the drawings.

The sheave tower at this point is a simple framework made with four light wooden vertical posts, diagonal rods, X-braces and adjustable steel-rod guys. It has overhanging caps, with

two carrier sheaves and one alignment sheave between them, at each end. Intermediate towers are substantially the same except for variations required to correspond with the varying inclination of the stringers.

The sixteen $1\frac{3}{4}$ -in. ropes required for the falsework cables are each 3300 ft. long, weigh about 17,000 lb. and were received coiled on separate reels delivered at the foot of the New York tower where each of them was painted with red lead as it was unwound from one reel and wound on another reel. Afterwards the reels were each mounted on an axle and the end of each rope reeled off and hauled over the top of the tower and back to the anchorage, where the ends were socketed with bridge sockets and attached to the anchor bars.


Everything being in readiness and the tide being slack, at flood, four of the reels were lifted by a floating derrick, loaded on a barge and towed across the river to the opposite tower pier, the ropes unwinding and dropping to the bottom of the river as the barge advanced. This operation required about 10 minutes, during which time the river at this point was practically closed to navigation by police patrol and United States harbor

The rope was then very carefully adjusted by pulling it into the exact catenary required as determined by elevations previously computed, and checked by levels given by instruments located in the main towers. The adjustment was made with such precision that the ropes in each cable are exactly uniform and probably do not vary more than an inch from their calculated positions. Additional checks were secured by taking angles with transits located on the piers. About $1\frac{1}{2}$ to 2 minutes were required to hoist each rope from its position on the river bottom to the required elevation, during which time, of course, the river traffic was again interrupted under control of the patrol and harbor boats, as mentioned in a preceding paragraph.


Simplifying School Heating and Ventilating Apparatus.

The purchase of additional apparatus to secure uniform and reliable operation has sometimes become necessary with certain classes of designs of heating and ventilating apparatus for school buildings, and studies along these lines have resulted in the development of a new arrangement of equipment by Mr. S. R. Lewis, which was discussed by him in a paper, from which the following notes are taken, before the recent Niagara Falls meeting of the American Society of Heating and Ventilating Engineers.


Mr. Lewis states that if there is any such thing as a standard type of heating and ventilating ap-




Footbridge Cable Saddle at Tower.



Details at Anchorage.




AT TOWERS



AT ANCHORAGE

Supporting Beams for Footbridge Cable Saddles.



Footbridge Cable Saddle at Anchorage.

boats. The barge was towed by three tugs, two at one end and one at the other. After being thus placed, all of them were unwound from their reels and coiled on the deck of a barge moored to the Brooklyn tower pier. The ends of the ropes were then pulled up to the tops of the tower by a hoisting engine located on the anchorage pier, were led through the tower saddles and were pulled down to the anchorage pier by a two-part tackle made by a line having both ends carried to separate drums of the hoisting engine. The bight of this line engaged a sheave supported from a $\frac{7}{8}$ -in. carrier rope, stretched at an angle of about 30 deg. from the top of the tower to the anchorage pier. As the falsework rope had an excess of length it was necessary to take up about 135 ft. of it, which was supported from the carrier rope as the line was hoisted about 230 ft. from the river bottom, to the required position at a clear height of 170 ft. above the water.

After the end was taken to the anchor pier about 20 ft. was cut off and the socket lead on.

After the ropes for each of the four cables were adjusted and connected together, the construction of the platforms on them was immediately commenced and rapidly prosecuted. All the woodwork had been previously cut to length, framed, bored and marked and was hoisted to the tops of the towers by two derricks located on each tower. The floorbeams were slipped down on the cables toward the center of the span and toward the anchorages, spaced and maintained in position by the stringers connected to them, after which the sheave towers were erected on the platforms, practically completing the falsework.

The bridge is being built under the direction of the Department of Bridges of the City of New York, Mr. J. W. Stevenson, commissioner; Mr. C. M. Ingersoll, Jr., chief engineer; Mr. Alexander Johnson, consulting engineer; Mr. D. E. Baxter, assistant engineer in charge of construction, and Mr. A. I. Perry, assistant engineer in charge of design. Mr. L. N. Gross is superintendent of erection for the Glyndon Contracting Co.

paratus for school buildings in this country, the equipment would perhaps be described as follows: The boilers are of the ordinary horizontal return tubular type, and are operated at comparatively high pressure. The fan is engine-driven, and the exhaust steam from the engine is used in the heating system. The customary pressure-reducing valve, back-pressure valve, grease extractor, etc., are installed, and the water of condensation is returned to the boilers by an automatic pump and receiver. The air is tempered for cool air supply to the building by approximately one-third of the heating coils prior to admission to the fan, and heated for warming the building by approximately two-thirds of the heating coils set in the fan outlet.

This system, Mr. Lewis states, when carefully designed and intelligently operated, is probably more economical in operation than any other. If, however, for any reason the fan cannot be operated, the warm air will all go to the nearest and warmest rooms, and those with the greatest ex-