

HistoricBridges.org - National Bridge Inventory Data Sheet

2010 Inventory

The National Bridge Inventory contains data submitted by state transportation departments to the Federal Highway Administration in coded format.

Form Interface Design: www.historicbridges.org. Data Conversion Assistance By www.bridgehunter.com. None of the involved parties make any guarantee of accuracy.

Basic Information

Pennsylvania [42]	Luzerne County [079]	Pittston [61048]	PITTSTON / W PITTSTON	41-19-28 = 41.324444	075-47-35 = - 75.793056
407303230500040	Highway agency district 4	Owner County Highway Agency [02]	Maintenance responsibility	County Highway Agency [02]	
Route 0		WATER ST	Toll On free road [3]	Features intersected Susq Riv/ Luz & Susq RR	
Design - main	Steel [3]	Design - approach		Kilometerpoint	0 km = 0.0 mi
5	Truss - Thru [10]	0	Other [00]	Year built	1914
				Year reconstructed	1984
				Skew angle	12
				Structure Flared	
				Historical significance	Bridge is not eligible for the NRHP. [5]
Total length	309.7 m = 1016.1 ft	Length of maximum span	61.6 m = 202.1 ft	Deck width, out-to-out	6.7 m = 22.0 ft
Inventory Route, Total Horizontal Clearance	6.4 m = 21.0 ft	Curb or sidewalk width - left	1.6 m = 5.2 ft	Curb or sidewalk width - right	0 m = 0.0 ft
Deck structure type	Concrete Cast-in-Place [1]				
Type of wearing surface	Monolithic Concrete (concurrently placed with structural deck) [1]				
Deck protection					
Type of membrane/wearing surface					

Weight Limits

Bypass, detour length	Method to determine inventory rating	Load Factor(LF) [1]	Inventory rating	25.4 metric ton = 27.9 tons
0.1 km = 0.1 mi	Method to determine operating rating	Load Factor(LF) [1]	Operating rating	42.6 metric ton = 46.9 tons
	Bridge posting	Equal to or above legal loads [5]	Design Load	M 13.5 / H 15 [2]

Functional Details

Average Daily Traffic	8665	Average daily truck traffi	5	%	Year	2008	Future average daily traffic	10400	Year	2028
Road classification	Minor Arterial (Urban) [16]		Lanes on structure	2		Approach roadway width	6.4 m = 21.0 ft			
Type of service on bridge	Highway-pedestrian [5]		Direction of traffic	2 - way traffic [2]		Bridge median				
Parallel structure designation	No parallel structure exists. [N]									
Type of service under bridge	Railroad-waterway [7]		Lanes under structure	0		Navigation control				
Navigation vertical clearanc	0 = N/A		Navigation horizontal clearance	0 = N/A						
Minimum navigation vertical clearance, vertical lift bridge	0 m = 0.0 ft					Minimum vertical clearance over bridge roadway	5 m = 16.4 ft			
Minimum lateral underclearance reference feature	Railroad beneath structure [R]									
Minimum lateral underclearance on right	0 = N/A					Minimum lateral underclearance on left	0 = N/A			
Minimum Vertical Underclearance	7 m = 23.0 ft		Minimum vertical underclearance reference feature	Railroad beneath structure [R]						
Appraisal ratings - underclearances	Basically intolerable requiring high priority of corrective action [3]									

Repair and Replacement Plans

Type of work to be performed	Work done by	Work to be done by owner's forces [2]		
Bridge rehabilitation because of general structure deterioration or inadequate strength. [35]	Bridge improvement cost	0	Roadway improvement cost	0
	Length of structure improvement	314 m = 1030.2 ft	Total project cost	1000
	Year of improvement cost estimate			
	Border bridge - state		Border bridge - percent responsibility of other state	
	Border bridge - structure number			

Inspection and Sufficiency

Structure status	Open, posting recommended but not legally implemented [B]	Appraisal ratings - structural	Meets minimum tolerable limits to be left in place as is [4]
Condition ratings - superstructure	Poor [4]	Appraisal ratings - roadway alignment	Somewhat better than minimum adequacy to tolerate being left in place as is [5]
Condition ratings - substructure	Fair [5]	Appraisal ratings - deck geometry	Basically intolerable requiring high priority of replacement [2]
Condition ratings - deck	Fair [5]		
Scour	Bridge foundations determined to be stable for the assessed or calculated scour condition. [8]		
Channel and channel protection	Bank protection is being eroded. River control devices and/or embankment have major damage. Trees and rush restrict the channel. [5]		
Appraisal ratings - water adequacy	Superior to present desirable criteria [9]	Status evaluation	Structurally deficient [1]
Pier or abutment protection		Sufficiency rating	40.7
Culverts	Not applicable. Used if structure is not a culvert. [N]		
Traffic safety features - railings			
Traffic safety features - transitions	Inspected feature meets currently acceptable standards. [1]		
Traffic safety features - approach guardrail	Inspected feature meets currently acceptable standards. [1]		
Traffic safety features - approach guardrail ends	Inspected feature meets currently acceptable standards. [1]		
Inspection date	August 2008 [0808]	Designated inspection frequency	24 Months
Underwater inspection	Every two years [Y24]	Underwater inspection date	June 2007 [0607]
Fracture critical inspection	Every two years [Y24]	Fracture critical inspection date	August 2008 [0808]
Other special inspection	Every two years [Y24]	Other special inspection date	October 2009 [1009]