

HistoricBridges.org - National Bridge Inventory Data Sheet

2013 Inventory

The National Bridge Inventory contains data submitted by state transportation departments to the Federal Highway Administration in coded format.

Form Interface Design: www.historicbridges.org. Data Conversion Assistance By www.bridgehunter.com. None of the involved parties make any guarantee of accuracy.

Basic Information

Washington [53]	Benton County [005]	Unknown [00000]	4.9 E JCT SR 240	46-38-30.00 = 46.641667	119-43-42.00 = -119.728333
0007619A0000000	Highway agency district 5	Owner State Highway Agency [01]	Maintenance responsibility	State Highway Agency [01]	
Route 24		SR 24	Toll On free road [3]	Features intersected COLUMBIA RIVER	
Design - main	Steel [3]	Design - approach	Prestressed concrete continuous [6]	Kilometerpoint	7015.2 km = 4349.4 mi
3	Truss - Thru [10]	14	Stringer/Multi-beam or girder [02]	Year built	1965
				Year reconstructed	N/A [0000]
				Skew angle	0
				Structure Flared	
				Historical significance	Bridge is not eligible for the NRHP. [5]
Total length	604.1 m = 1982.1 ft	Length of maximum span	80.5 m = 264.1 ft	Deck width, out-to-out	10.3 m = 33.8 ft
Inventory Route, Total Horizontal Clearance	8.5 m = 27.9 ft	Curb or sidewalk width - left	0.6 m = 2.0 ft	Curb or sidewalk width - right	0.6 m = 2.0 ft
Deck structure type	Concrete Cast-in-Place [1]				
Type of wearing surface	Monolithic Concrete (concurrently placed with structural deck) [1]				
Deck protection					
Type of membrane/wearing surface					

Weight Limits

Bypass, detour length	Method to determine inventory rating	Load Factor(LF) [1]	Inventory rating	35.1 metric ton = 38.6 tons
19.9 km = 12.3 mi	Method to determine operating rating	Load Factor(LF) [1]	Operating rating	59.4 metric ton = 65.3 tons
	Bridge posting	Equal to or above legal loads [5]	Design Load	MS 18 / HS 20 [5]

Functional Details

Average Daily Traffic	3854	Average daily truck traffi	22	%	Year	2010	Future average daily traffic	5396	Year	2030
Road classification	Minor Arterial (Rural) [06]		Lanes on structure	2		Approach roadway width	9.8 m = 32.2 ft			
Type of service on bridge	Highway [1]		Direction of traffic	2 - way traffic [2]		Bridge median				
Parallel structure designation	No parallel structure exists. [N]									
Type of service under bridge	Waterway [5]		Lanes under structure	0		Navigation control	Navigation control on waterway (bridge permit required). [1]			
Navigation vertical clearanc	3 m = 9.8 ft		Navigation horizontal clearance	76.2 m = 250.0 ft						
Minimum navigation vertical clearance, vertical lift bridge			Minimum vertical clearance over bridge roadway	4.95 m = 16.2 ft						
Minimum lateral underclearance reference feature	Feature not a highway or railroad [N]									
Minimum lateral underclearance on right	0 = N/A					Minimum lateral underclearance on left	0 = N/A			
Minimum Vertical Underclearance	0 = N/A		Minimum vertical underclearance reference feature	Feature not a highway or railroad [N]						
Appraisal ratings - underclearances	N/A [N]									

Repair and Replacement Plans

Type of work to be performed	Work done by	Work to be done by contract [1]		
Bridge rehabilitation because of general structure deterioration or inadequate strength. [35]	Bridge improvement cost	35763000	Roadway improvement cost	7153000
	Length of structure improvement	619.4 m = 2032.3 ft	Total project cost	71526000
	Year of improvement cost estimate	2010		
	Border bridge - state		Border bridge - percent responsibility of other state	
	Border bridge - structure number			

Inspection and Sufficiency

Structure status	Open, no restriction [A]	Appraisal ratings - structural	Equal to present minimum criteria [6]
Condition ratings - superstructure	Satisfactory [6]	Appraisal ratings - roadway alignment	Equal to present minimum criteria [6]
Condition ratings - substructure	Satisfactory [6]	Appraisal ratings - deck geometry	Meets minimum tolerable limits to be left in place as is [4]
Condition ratings - deck	Satisfactory [6]		
Scour	Bridge foundations determined to be stable for the assessed or calculated scour condition. [8]		
Channel and channel protection	Banks are protected or well vegetated. River control devices such as spur dikes and embankment protection are not required or are in a stable condition. [8]		
Appraisal ratings - water adequacy	Equal to present desirable criteria [8]	Status evaluation	
Pier or abutment protection	Navigation protection not required [1]	Sufficiency rating	58
Culverts	Not applicable. Used if structure is not a culvert. [N]		
Traffic safety features - railings	Inspected feature meets currently acceptable standards. [1]		
Traffic safety features - transitions	Inspected feature meets currently acceptable standards. [1]		
Traffic safety features - approach guardrail	Inspected feature meets currently acceptable standards. [1]		
Traffic safety features - approach guardrail ends			
Inspection date	March 2012 [0312]	Designated inspection frequency	24 Months
Underwater inspection	Unknown [Y60]	Underwater inspection date	September 2012 [0912]
Fracture critical inspection	Every two years [Y24]	Fracture critical inspection date	March 2012 [0312]
Other special inspection	Not needed [N]	Other special inspection date	