The National Bridge Inventory contains data submitted by state transportion departments to the Federal Highway Administration in coded format.

Form Interface Design: www.historicbridges.org. Data Conversion Assistance By www.bridgehunter.com. None of the involved parties make any guarantee of accuracy.

| Basic Information | | | | | | | 42-34-58 = | 088-55-21 = - | | |
|---|----------------|----------------------------|---------------------------------|---|------------------|--------------------|------------------|---------------------|--|--|
| Wisconsin [55] | Rock County [1 | 05] | Turtle [81050] 0.3M N JCT CTH J | | J | | | 88.922500 | | |
| P53015300000000 Highway agency district 1 | | agency district 1 | Owner Town or Townsh | Town or Township Highway Agency [03] Maintenance responsibility | | | Town or Township | Highway Agency [03] | | |
| Route 0 | East [2] | LRD SMITH RD | Toll On fre | ee road [3] | Features interse | cted TURTLE CRI | EEK | | | |
| Design - Steel [3] main Truss - Thr | u [10] | Design - approach 0 Other | [00] | Kilometerpoint Year built 1910 Skew angle 0 | Structure F | | , | | | |
| Historical significance Bridge is not eligible for the NRHP. [5] Total length 37.2 m = 122.1 ft Length of maximum span 36.6 m = 120.1 ft Deck width, out-to-out 4.9 m = 16.1 ft Bridge roadway width, curb-to-curb 4.5 m = 14.8 ft | | | | | | | | | | |
| Inventory Route, Total Horizontal Clearance 6.7 m = 22.0 ft Curb or sidewalk width - left 0 m = 0.0 ft Curb or sidewalk width | | | | | | walk width - right | 0 m = 0.0 ft | | | |
| Deck structure type | | Open Grating [3] | | | | | | | | |
| Type of wearing surface | | Other [9] | Other [9] | | | | | | | |
| Deck protection | | | | | | | | | | |
| Type of membrane/wearing surface Unknown [8] | | | | | | | | | | |
| Weight Limits | | | | | | | | | | |
| | | etermine inventory rating | Load Factor(LF) [1] | | Inventory rating | 8.1 metric ton = 8 | 3.9 tons | | | |
| 0.4 km = 0.2 mi | Method to d | etermine operating rating | Load Factor(LF) [1] | | Operating rating | 16.2 metric ton = | 17.8 tons | | | |
| | Bridge posti | ng 20.0 - 29.9 % belo | w [2] | | Design Load | | | | | |

| Functional Details | | | | | | | |
|---|---|--|--|--|--|--|--|
| Average Daily Traffic 1 Average daily truck | traffi 0 % Year 2008 Future average daily traffic 1 Year 2029 | | | | | | |
| Road classification Local (Rural) [09] | Lanes on structure 1 Approach roadway width 6.7 m = 22.0 ft | | | | | | |
| Type of service on bridge Highway [1] | Direction of traffic One lane bridge for 2 - way traffic [3] Bridge median | | | | | | |
| Parallel structure designation No parallel structure exi | ists. [N] | | | | | | |
| Type of service under bridge Waterway [5] | Lanes under structure 0 Navigation control | | | | | | |
| Navigation vertical clearanc 0 = N/A | Navigation horizontal clearance 0 = N/A | | | | | | |
| Minimum navigation vertical clearance, vertical lift bridge | 0 m = 0.0 ft Minimum vertical clearance over bridge roadway 3.44 m = 11.3 ft | | | | | | |
| Minimum lateral underclearance reference feature Feature | re not a highway or railroad [N] | | | | | | |
| Minimum lateral underclearance on right 0 = N/A Minimum lateral underclearance on left 0 = N/A | | | | | | | |
| Minimum Vertical Underclearance 0 = N/A | Minimum vertical underclearance reference feature Feature not a highway or railroad [N] | | | | | | |
| Appraisal ratings - underclearances N/A [N] | | | | | | | |
| | | | | | | | |
| Repair and Replacement Plans | | | | | | | |
| Type of work to be performed W | /ork done by Work to be done by owner's forces [2] | | | | | | |
| Replacement of bridge or other structure because of substandard load carrying capacity or substantial | ridge improvement cost 320000 Roadway improvement cost 32000 | | | | | | |
| | ength of structure improvement 41.8 m = 137.1 ft Total project cost 480000 | | | | | | |
| Ye | ear of improvement cost estimate 2010 | | | | | | |
| Bo | order bridge - state Border bridge - percent responsibility of other state | | | | | | |
| Вс | order bridge - structure number | | | | | | |

| Inspection and Sufficiency | | | | | | | | |
|---|------------------------------------|---|--|--|----------------------------|--|--|--|
| Structure status Posted for load [P] | | Appraisal ratings - structural | Basically intolerable requiring high priority of replacement [2] | | | | | |
| Condition ratings - superstructur Fair [5] | | Appraisal ratings - roadway alignment | Basically into | igh priority of corrrective action [3] | | | | |
| Condition ratings - substructure | Fair [5] | Appraisal ratings - deck geometry | Basically intolerable requiring high priority of replacement [2] | | | | | |
| Condition ratings - deck | Satisfactory [6] | | | | | | | |
| Scour | Bridge is scour critical; bridge | Bridge is scour critical; bridge foundations determined to be unstable. [3] | | | | | | |
| Channel and channel protection | Not applicable. [N] | Not applicable. [N] | | | | | | |
| Appraisal ratings - water adequac | Equal to present desirable cri | Equal to present desirable criteria [8] | | | Structurally deficient [1] | | | |
| Pier or abutment protection | | | | ufficiency rating | 22 | | | |
| Culverts Not applicable. Used | if structure is not a culvert. [N] | | | | | | | |
| Traffic safety features - railings | | | | | | | | |
| Traffic safety features - transition | ns | | | | | | | |
| Traffic safety features - approach | n guardrail | | | | | | | |
| Traffic safety features - approach | n guardrail ends | | | | | | | |
| Inspection date May 2010 [0510] Designated inspection frequency 24 Months | | | | | | | | |
| Underwater inspection Not needed [N] | | Underwater inspec | ction date | | | | | |
| Fracture critical inspection | Every two years [Y24] | two years [Y24] Fracture critical in | | May 2010 [0510 | 0] | | | |
| Other special inspection | Not needed [N] | Other special insp | ection date | | | | | |